



(12) **United States Patent**  
**Corson et al.**

(10) **Patent No.:** **US 9,313,784 B2**  
(45) **Date of Patent:** **Apr. 12, 2016**

(54) **STATE SYNCHRONIZATION OF ACCESS ROUTERS**

(71) Applicant: **QUALCOMM Incorporated**, San Diego, CA (US)

(72) Inventors: **Mathew Scott Corson**, Gillette, NJ (US); **Georgios Tsirtsis**, London (GB); **Vincent Douglas Park**, Budd Lake, NJ (US)

(73) Assignee: **QUALCOMM Incorporated**, San Diego, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 493 days.

(21) Appl. No.: **13/777,458**

(22) Filed: **Feb. 26, 2013**

(65) **Prior Publication Data**

US 2013/0208709 A1 Aug. 15, 2013

**Related U.S. Application Data**

(62) Division of application No. 11/486,650, filed on Jul. 14, 2006, now Pat. No. 9,066,344.

(60) Provisional application No. 60/718,363, filed on Sep. 19, 2005, provisional application No. 60/796,653, filed on May 1, 2006.

(51) **Int. Cl.**  
**H04B 7/00** (2006.01)  
**H04B 15/00** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **H04W 72/0426** (2013.01); **H04W 8/12** (2013.01); **H04W 40/02** (2013.01); **H04W 60/04** (2013.01)

(58) **Field of Classification Search**  
CPC ..... H04W 56/00; H04W 56/0035; H04W 56/0045; H04W 72/0426; H04W 8/12; H04W 40/02; H04W 60/04; H04W 36/18; H04W

12/06; H04W 36/0038; H04B 7/2693; H04H 20/67; H04L 63/164; H04L 63/123; H04L 9/0891; H04L 9/3247; H04L 9/3239; H04L 45/02; H04L 45/26; H04L 63/08  
USPC ..... 455/67.11, 534, 432.1, 524, 502; 370/338, 331, 312, 401, 468, 404  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,679,244 A 7/1987 Kawasaki et al.  
4,833,701 A 5/1989 Comroe et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

AU 2002353616 5/2003  
CN 1043052 A 6/1990

(Continued)

**OTHER PUBLICATIONS**

3GPP, "3rd Generation Partnership Project, Technical Specification Group Radio Access Network, E-UTRAN Mobility Evaluation and Enhancement, (Release 9)", 3GPP Draft, R1-090856 TP for TR for Mobility Studies, 3rd Generation Partnership Project (3GPP), Mobile Competence Centre, 650, Route Des Lucioles, F-06921 Sophia-Antipolis Cedex, France, no. Athens, Greece, Feb. 3, 2009, 16 pgs., XP050318707.

(Continued)


*Primary Examiner* — Mahendra Patel

(74) *Attorney, Agent, or Firm* — Liem T. Do

(57) **ABSTRACT**

Embodiments describe synchronizing access routers with wireless terminal state information. According to an embodiment is a wireless terminal that transmits a message that includes an address for at least two access routers. State change information can optionally be included in the message. According to another embodiment is an access router that receives a state change notification from a wireless device or another access router. The state change notification is updated in the access router. An acknowledgment confirming the updated state change may be sent to the wireless terminal. Dynamic state synchronization is provided with minimal communication with wireless terminal.

**60 Claims, 19 Drawing Sheets**



(51)	<b>Int. Cl.</b>		6,055,236	A	4/2000	Nessett et al.
	<b>H04W 72/04</b>	(2009.01)	6,055,428	A	4/2000	Soliman
	<b>H04W 8/12</b>	(2009.01)	6,073,021	A	6/2000	Kumar et al.
	<b>H04W 40/02</b>	(2009.01)	6,078,575	A	6/2000	Dommetty et al.
	<b>H04W 60/04</b>	(2009.01)	6,084,969	A	7/2000	Wright et al.
(56)			6,092,111	A	7/2000	Scivier et al.
			6,094,427	A	7/2000	Yi
			6,097,952	A	8/2000	Kawabata
			6,101,394	A	8/2000	Illidge
			6,134,226	A	10/2000	Reed et al.
<b>References Cited</b>			6,137,787	A	10/2000	Chawla et al.
U.S. PATENT DOCUMENTS			6,144,671	A	11/2000	Perinpanathan et al.
4,901,307	A	2/1990	6,151,502	A	11/2000	Padovani et al.
5,056,109	A	10/1991	6,157,668	A	12/2000	Gilhausen et al.
5,095,529	A	3/1992	6,157,833	A	12/2000	Lawson-Jenkins et al.
5,117,502	A	5/1992	6,157,978	A	12/2000	Ng et al.
5,128,938	A	7/1992	6,160,798	A	12/2000	Reed et al.
5,200,952	A	4/1993	6,161,008	A	12/2000	Lee et al.
5,208,837	A	5/1993	6,163,692	A	12/2000	Chakrabarti et al.
5,210,787	A	5/1993	6,195,552	B1	2/2001	Jeong et al.
5,229,992	A	7/1993	6,195,705	B1	2/2001	Leung
5,247,516	A	9/1993	6,201,971	B1	3/2001	Purnadi et al.
5,251,209	A	10/1993	6,225,888	B1	5/2001	Juopperi
5,267,261	A	11/1993	6,256,300	B1	7/2001	Ahmed et al.
5,268,933	A	12/1993	6,272,129	B1	8/2001	Dynarski et al.
5,325,432	A	6/1994	6,275,712	B1	8/2001	Gray et al.
5,333,178	A	7/1994	6,285,251	B1	9/2001	Dent et al.
5,369,781	A	11/1994	6,285,665	B1	9/2001	Chuah
5,387,905	A	2/1995	6,300,887	B1	10/2001	Le
5,388,102	A	2/1995	6,308,080	B1	10/2001	Burt et al.
5,420,909	A	5/1995	6,308,267	B1	10/2001	Gremmelmaier
5,426,395	A	6/1995	6,345,043	B1	2/2002	Hsu
5,450,405	A	9/1995	6,347,091	B1	2/2002	Wallentin et al.
5,461,645	A	10/1995	6,353,616	B1	3/2002	Elwalid et al.
5,463,617	A	10/1995	6,360,100	B1	3/2002	Grob et al.
5,465,391	A	11/1995	6,366,561	B1	4/2002	Bender
5,473,605	A	12/1995	6,366,577	B1	4/2002	Donovan
5,490,139	A	2/1996	6,370,380	B1	4/2002	Norefors et al.
5,491,835	A	2/1996	6,389,008	B1	5/2002	Lupien et al.
5,509,027	A	4/1996	6,397,065	B1	5/2002	Huusko et al.
5,511,232	A	4/1996	6,400,703	B1	6/2002	Park et al.
5,513,381	A	4/1996	6,400,722	B1	6/2002	Chuah et al.
5,539,925	A	7/1996	6,430,213	B1	8/2002	Dafesh
5,542,108	A	7/1996	6,434,134	B1	8/2002	La Porta et al.
5,561,841	A	10/1996	6,445,922	B1	9/2002	Hiller et al.
5,566,366	A	10/1996	6,446,127	B1	9/2002	Schuster et al.
5,572,528	A	11/1996	6,449,481	B1	9/2002	Kwon et al.
5,574,720	A	11/1996	6,456,604	B1	9/2002	Lee et al.
5,590,175	A	12/1996	6,463,055	B1	10/2002	Lupien et al.
5,590,396	A	12/1996	6,466,964	B1	10/2002	Leung et al.
5,594,943	A	1/1997	6,473,418	B1	10/2002	Laroia et al.
5,594,948	A	1/1997	6,477,150	B1	11/2002	Maggenti et al.
5,625,882	A	4/1997	6,487,170	B1	11/2002	Chen et al.
5,627,882	A	5/1997	6,487,407	B2	11/2002	Goldberg et al.
5,634,197	A	5/1997	6,490,564	B1	12/2002	Doddrill et al.
5,694,433	A	12/1997	6,493,725	B1	12/2002	Iwai et al.
5,694,548	A	12/1997	6,496,505	B2	12/2002	La Porta et al.
5,722,044	A	2/1998	6,496,704	B2	12/2002	Yuan
5,737,328	A	4/1998	6,498,934	B1	12/2002	Muller
5,794,137	A	8/1998	6,505,047	B1	1/2003	Palkisto
5,806,007	A	9/1998	6,510,144	B1	1/2003	Dommetty et al.
5,854,785	A	12/1998	6,510,153	B1	1/2003	Inoue et al.
5,870,427	A	2/1999	6,512,754	B2	1/2003	Feder et al.
5,884,196	A	3/1999	6,516,352	B1	2/2003	Booth et al.
5,898,922	A	4/1999	6,519,254	B1	2/2003	Chuah et al.
5,901,362	A	5/1999	6,519,457	B1	2/2003	Jiang et al.
5,903,559	A	5/1999	6,529,732	B1	3/2003	Vainiomaki et al.
5,953,653	A	9/1999	6,535,493	B1	3/2003	Lee et al.
5,974,036	A	10/1999	6,535,739	B1	3/2003	Chen et al.
5,978,366	A	11/1999	6,539,225	B1	3/2003	Lee
5,987,323	A	11/1999	6,546,252	B1	4/2003	Jetzek et al.
6,011,969	A	1/2000	6,553,227	B1	4/2003	Ho et al.
6,016,316	A	1/2000	6,563,919	B1	5/2003	Aravamudhan et al.
6,018,521	A	1/2000	6,567,416	B1	5/2003	Chuah
6,021,123	A	2/2000	6,567,664	B1	5/2003	Bergenswall et al.
6,021,326	A	2/2000	6,571,095	B1	5/2003	Koodli
6,031,863	A	2/2000	6,571,289	B1	5/2003	Montenegro
6,034,950	A	3/2000	6,578,085	B1	6/2003	Khalil et al.
6,043,707	A	3/2000	6,584,093	B1	6/2003	Salama et al.
6,049,543	A	4/2000				

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,587,680 B1 *	7/2003	Ala-Laurila .....	H04L 63/08 380/248	7,187,928 B1	3/2007	Senn et al.
6,611,506 B1	8/2003	Huang et al.		7,197,318 B2	3/2007	Schwarz et al.
6,611,547 B1	8/2003	Rauhala		7,233,583 B2	6/2007	Asthana et al.
6,615,236 B2	9/2003	Donovan et al.		7,233,794 B2	6/2007	Grob et al.
6,631,122 B1	10/2003	Arunachalam et al.		7,257,402 B2	8/2007	Khalil et al.
6,631,254 B1	10/2003	Wilson et al.		7,263,357 B2	8/2007	Lee et al.
6,636,498 B1	10/2003	Leung		7,266,100 B2	9/2007	Le et al.
6,640,248 B1	10/2003	Jorgensen		7,269,145 B2	9/2007	Koo et al.
6,650,901 B1	11/2003	Schuster et al.		7,272,122 B2	9/2007	Trossen et al.
6,654,363 B1	11/2003	Li et al.		7,283,495 B2	10/2007	Lee et al.
6,668,166 B1	12/2003	Kanabar		7,283,511 B2	10/2007	Hans et al.
6,671,512 B2	12/2003	Laakso		7,290,063 B2	10/2007	Kalliokulju et al.
6,678,735 B1	1/2004	Orton et al.		7,292,592 B2	11/2007	Rune
6,680,943 B1	1/2004	Gibson et al.		7,315,554 B2	1/2008	Baum et al.
6,690,936 B1	2/2004	Lundh		7,330,542 B2	2/2008	Kauhanen et al.
6,701,155 B2	3/2004	Sarkkinen et al.		7,333,452 B2	2/2008	Lim
6,708,031 B2	3/2004	Purnadi et al.		7,336,753 B2	2/2008	Hasson et al.
6,714,524 B1	3/2004	Kim et al.		7,336,953 B2	2/2008	Kim et al.
6,714,777 B1	3/2004	Naqvi et al.		7,369,855 B2	5/2008	ONeill et al.
6,714,788 B2	3/2004	Voyer		7,369,859 B2	5/2008	Gallagher
6,724,267 B2	4/2004	Kim		7,376,101 B2	5/2008	Shim et al.
6,728,365 B1	4/2004	Li et al.		7,389,110 B2	6/2008	Lee
6,731,932 B1	5/2004	Rune et al.		7,391,741 B2	6/2008	Kang
6,754,482 B1	6/2004	Torabi		7,403,789 B2	7/2008	Takano et al.
6,754,492 B1	6/2004	Stammers et al.		7,408,917 B1	8/2008	Kyung et al.
6,763,007 B1	7/2004	La Porta et al.		7,408,950 B2	8/2008	Okuyama
6,768,908 B1	7/2004	Jalloul et al.		7,409,428 B1	8/2008	Brabec et al.
6,771,962 B2	8/2004	Saifullah et al.		7,418,264 B2	8/2008	Kim
6,785,256 B2	8/2004	O'Neill		7,420,957 B2	9/2008	Kim et al.
6,807,421 B1	10/2004	Ahmavaara		7,460,504 B2	12/2008	Tsirtsis et al.
6,842,621 B2	1/2005	Labun et al.		7,492,762 B2	2/2009	Chowdhury
6,842,630 B2	1/2005	Periyalwar		7,499,401 B2	3/2009	Buddhikot et al.
6,862,446 B2	3/2005	ONeill et al.		7,505,765 B2	3/2009	Frangione et al.
6,879,690 B2	4/2005	Faccin et al.		7,515,561 B2	4/2009	Koodli et al.
6,901,063 B2	5/2005	Vayanos et al.		7,525,940 B2	4/2009	Trossen et al.
6,917,605 B2	7/2005	Kakemizu et al.		7,529,239 B2	5/2009	Seppanen
6,937,566 B1	8/2005	Forslow		7,567,639 B2	7/2009	Huh et al.
6,947,401 B2	9/2005	El-Malki et al.		7,583,592 B2	9/2009	Park et al.
6,950,650 B2	9/2005	Roeder		7,593,364 B2	9/2009	Asthana
6,954,442 B2	10/2005	Tsirtsis et al.		7,623,493 B2	11/2009	Baba et al.
6,961,579 B2	11/2005	Inukai et al.		7,653,415 B2	1/2010	Van Rooyen
6,965,585 B2	11/2005	Grilli et al.		7,668,541 B2	2/2010	ONeill et al.
6,970,445 B2	11/2005	O'Neill et al.		7,672,254 B2	3/2010	Kim et al.
6,990,088 B2	1/2006	Madour		7,702,309 B2	4/2010	Faccin et al.
6,990,337 B2	1/2006	ONeill et al.		7,706,739 B2	4/2010	Kjellberg
6,990,339 B2	1/2006	Turanyi et al.		7,729,350 B2	6/2010	Singh et al.
6,990,343 B2	1/2006	Lefkowitz		7,742,781 B2	6/2010	Chen et al.
6,992,994 B2	1/2006	Das et al.		7,773,947 B2	8/2010	Gerlach
6,993,332 B2	1/2006	Pedersen et al.		7,869,803 B2	1/2011	Corson et al.
6,996,379 B2	2/2006	Khorram		7,882,346 B2	2/2011	ONeill et al.
7,003,311 B2	2/2006	Ebata et al.		7,962,142 B2	6/2011	O'Neill et al.
7,006,826 B2	2/2006	Cao et al.		8,112,102 B2	2/2012	Fischer
7,016,317 B1	3/2006	Pathak et al.		8,134,976 B2	3/2012	Wallace et al.
7,027,400 B2	4/2006	O'Neill		8,144,664 B2	3/2012	Pani et al.
7,027,449 B2	4/2006	Garcia-Luna-Aceves et al.		8,165,587 B2	4/2012	Dahlen et al.
7,047,009 B2	5/2006	Laroia et al.		8,184,615 B2	5/2012	Tsirtsis et al.
7,068,640 B2	6/2006	Kakemizu et al.		8,229,120 B2	7/2012	Iwamura et al.
7,068,654 B1	6/2006	Joseph et al.		8,509,799 B2	8/2013	Park et al.
7,069,040 B2	6/2006	Iwanaga et al.		8,583,044 B2	11/2013	Dua
7,079,511 B2	7/2006	Abrol et al.		2001/0019545 A1	9/2001	Okubo et al.
7,089,008 B1	8/2006	Back et al.		2002/0061009 A1	5/2002	Sorensen
7,096,014 B2	8/2006	Haverinen et al.		2002/0064144 A1	5/2002	Einola et al.
7,110,727 B2	9/2006	Dekker		2002/0065785 A1	5/2002	Tsuda
7,116,646 B1	10/2006	Gustafson et al.		2002/0067706 A1	6/2002	Bautz et al.
7,116,654 B2	10/2006	Kim		2002/0075859 A1	6/2002	Mizell et al.
7,123,599 B2	10/2006	Yano et al.		2002/0082038 A1	6/2002	Mochizuki
7,130,291 B1	10/2006	Kim et al.		2002/0085518 A1	7/2002	Lim
7,133,456 B2	11/2006	Fehér		2002/0107908 A1	8/2002	Dharanikota
7,139,548 B2	11/2006	Hayashi et al.		2002/0114308 A1	8/2002	Takano et al.
7,155,236 B2	12/2006	Chen et al.		2002/0126701 A1	9/2002	Requena
7,161,913 B2	1/2007	Jung		2002/0136226 A1	9/2002	Christoffel et al.
7,167,447 B2	1/2007	Puuskari et al.		2002/0161927 A1	10/2002	Inoue et al.
7,177,641 B1	2/2007	Miernik et al.		2002/0168982 A1 *	11/2002	Sorokine ..... H04W 36/18 455/442
7,184,771 B1	2/2007	Mouly et al.		2002/0186679 A1	12/2002	Nakatsugawa et al.
				2002/0199012 A1	12/2002	Cable et al.
				2003/0009580 A1	1/2003	Chen et al.
				2003/0009582 A1	1/2003	Qiao et al.
				2003/0018774 A1	1/2003	Flinck et al.

(56)	<b>References Cited</b>			2006/0003768	A1	1/2006	Chiou
	U.S. PATENT DOCUMENTS			2006/0007936	A1	1/2006	Shrum, Jr. et al.
				2006/0029028	A1	2/2006	Kim et al.
				2006/0036733	A1*	2/2006	Fujimoto ..... H04L 61/2015 709/225
2003/0026220	A1	2/2003	Uhlik et al.	2006/0056348	A1	3/2006	Marinier et al.
2003/0027572	A1	2/2003	Karlsson et al.	2006/0067526	A1	3/2006	Faccin et al.
2003/0032430	A1	2/2003	Lee	2006/0069809	A1	3/2006	Serlet
2003/0036392	A1	2/2003	Yukie	2006/0089141	A1	4/2006	Ho et al.
2003/0051140	A1	3/2003	Buddhikot et al.	2006/0099948	A1	5/2006	Hoghooghi et al.
2003/0071417	A1	4/2003	Webb	2006/0099950	A1	5/2006	Klein et al.
2003/0078047	A1	4/2003	Lee et al.	2006/0104232	A1	5/2006	Gidwani
2003/0092441	A1	5/2003	Taha et al.	2006/0121883	A1	6/2006	Faccin
2003/0092444	A1	5/2003	Sengodan et al.	2006/0149845	A1	7/2006	Malin et al.
2003/0101307	A1	5/2003	Gemelli et al.	2006/0159082	A1*	7/2006	Cook ..... H04L 45/02 370/389
2003/0103496	A1	6/2003	Lakshmi Narayanan et al.	2006/0183479	A1	8/2006	Liu et al.
2003/0104814	A1	6/2003	Gwon et al.	2006/0217119	A1	9/2006	Bosch et al.
2003/0112766	A1	6/2003	Riedel et al.	2006/0221883	A1	10/2006	Damnjanovic et al.
2003/0119516	A1	6/2003	Tomishima et al.	2006/0230019	A1	10/2006	Hill et al.
2003/0137991	A1	7/2003	Doshi et al.	2006/0268924	A1	11/2006	Marinier et al.
2003/0204599	A1	10/2003	Trossen et al.	2006/0285520	A1	12/2006	Venkitaraman
2003/0214922	A1	11/2003	Shahrier	2007/0016637	A1	1/2007	Brawn et al.
2003/0216140	A1	11/2003	Chambert	2007/0019584	A1	1/2007	Qi et al.
2003/0217096	A1	11/2003	McKelvie et al.	2007/0064948	A1	3/2007	Tsirtsis et al.
2003/0227871	A1	12/2003	Hsu et al.	2007/0066918	A1	3/2007	Dewald et al.
2003/0236103	A1	12/2003	Tamaki et al.	2007/0076653	A1	4/2007	Park et al.
2004/0002362	A1	1/2004	Chuah et al.	2007/0076658	A1	4/2007	Park et al.
2004/0003070	A1*	1/2004	Fernald ..... H04L 12/2602 709/223	2007/0078999	A1	4/2007	Corson et al.
2004/0004736	A1	1/2004	Ogura et al.	2007/0083669	A1	4/2007	Tsirtsis et al.
2004/0004967	A1	1/2004	Nakatsugawa et al.	2007/0086389	A1	4/2007	Park et al.
2004/0008630	A1	1/2004	Corson et al.	2007/0091810	A1	4/2007	Kim et al.
2004/0008632	A1	1/2004	Hsu et al.	2007/0099618	A1	5/2007	Kim
2004/0015607	A1	1/2004	Bender et al.	2007/0105555	A1	5/2007	Miernik et al.
2004/0016551	A1	1/2004	Bennett	2007/0105584	A1	5/2007	Grob et al.
2004/0017792	A1	1/2004	Khaleghi et al.	2007/0121542	A1	5/2007	Lohr et al.
2004/0017798	A1	1/2004	Hurtta et al.	2007/0147283	A1	6/2007	Laroia et al.
2004/0018841	A1	1/2004	Trossen	2007/0147286	A1	6/2007	Laroia et al.
2004/0037264	A1	2/2004	Khawand	2007/0147377	A1	6/2007	Laroia et al.
2004/0076186	A1	4/2004	Chen et al.	2007/0149126	A1	6/2007	Rangan et al.
2004/0087319	A1	5/2004	Bos et al.	2007/0149194	A1	6/2007	Das et al.
2004/0090913	A1	5/2004	Scudder et al.	2007/0171875	A1	7/2007	Suda
2004/0090937	A1	5/2004	Chaskar et al.	2007/0189282	A1	8/2007	Lohr et al.
2004/0104544	A1	6/2004	Fan et al.	2007/0191054	A1	8/2007	Das et al.
2004/0116153	A1	6/2004	Kaminski et al.	2007/0191065	A1	8/2007	Lee et al.
2004/0120317	A1	6/2004	Forssell	2007/0195788	A1	8/2007	Vasamsetti et al.
2004/0139201	A1	7/2004	Chaudhary et al.	2008/0019293	A1	1/2008	Chang et al.
2004/0151148	A1	8/2004	Yahagi	2008/0031198	A1	2/2008	Hwang et al.
2004/0151193	A1	8/2004	Rune et al.	2008/0051091	A1	2/2008	Phan et al.
2004/0165551	A1	8/2004	Krishnamurthi et al.	2008/0074994	A1	3/2008	Jen
2004/0166898	A1	8/2004	Tajima	2008/0076424	A1	3/2008	Barber et al.
2004/0179544	A1	9/2004	Wilson et al.	2008/0089287	A1	4/2008	Sagfors et al.
2004/0192307	A1	9/2004	Watanabe et al.	2008/0146231	A1	6/2008	Huang et al.
2004/0192390	A1	9/2004	Tajima	2008/0160999	A1	7/2008	Eklund
2004/0218607	A1	11/2004	Hurtta et al.	2008/0240039	A1	10/2008	Parekh
2004/0228301	A1	11/2004	Rudolf et al.	2008/0242292	A1	10/2008	Koskela et al.
2004/0228304	A1	11/2004	Riedel et al.	2008/0253332	A1	10/2008	Ore et al.
2004/0242222	A1	12/2004	An et al.	2008/0259855	A1	10/2008	Yoon et al.
2004/0253954	A1	12/2004	Lee et al.	2008/0261600	A1	10/2008	Somasundaram et al.
2005/0014509	A1	1/2005	Semper et al.	2009/0029706	A1	1/2009	Prakash
2005/0020262	A1	1/2005	Kim	2009/0046573	A1	2/2009	Damnjanovic
2005/0020265	A1	1/2005	Funabiki et al.	2009/0175448	A1	7/2009	Watanabe et al.
2005/0053043	A1	3/2005	Rudolf et al.	2009/0181673	A1	7/2009	Barrett
2005/0058151	A1	3/2005	Yeh	2009/0190556	A1	7/2009	Venkitaraman
2005/0059417	A1	3/2005	Zhang et al.	2009/0191878	A1	7/2009	Hedqvist et al.
2005/0063324	A1*	3/2005	O'Neill ..... H04L 12/2856 370/310	2009/0274086	A1	11/2009	Petrovic et al.
2005/0063338	A1	3/2005	Tsui	2009/0285218	A1	11/2009	Adamczyk et al.
2005/0063389	A1	3/2005	Elliott et al.	2010/0080126	A1	4/2010	Higashida
2005/0079823	A1	4/2005	Kurek et al.	2011/0019614	A1	1/2011	O'Neill et al.
2005/0089043	A1	4/2005	Seckin et al.	2011/0039546	A1	2/2011	Narasimha et al.
2005/0090260	A1	4/2005	Semper et al.	2011/0039552	A1	2/2011	Narasimha et al.
2005/0128949	A1	6/2005	Ku et al.	2011/0051660	A1	3/2011	Arora et al.
2005/0128990	A1	6/2005	Eom et al.	2011/0103347	A1	5/2011	Dimou
2005/0141468	A1	6/2005	Kim et al.	2011/0250892	A1	10/2011	Gupta et al.
2005/0143072	A1	6/2005	Yoon et al.	2011/0268085	A1	11/2011	Barany et al.
2005/0201324	A1	9/2005	Zheng	2012/0087312	A1	4/2012	Laroia et al.
2005/0265303	A1	12/2005	Edwards et al.	2012/0327908	A1	12/2012	Gupta et al.
2005/0268153	A1	12/2005	Armstrong et al.				
2006/0002344	A1	1/2006	Ono et al.				

(56)

**References Cited****U.S. PATENT DOCUMENTS**

2013/0294324 A1 11/2013 Corson et al.  
 2015/0030003 A1 1/2015 O'Neill et al.

**FOREIGN PATENT DOCUMENTS**

CN 1344477 A 4/2002  
 CN 1345518 A 4/2002  
 CN 1416284 A 5/2003  
 CN 1481119 A 3/2004  
 CN 1490959 A 4/2004  
 CN 1514607 7/2004  
 CN 1553741 12/2004  
 CN 1859529 A 11/2006  
 EP 0740440 A2 10/1996  
 EP 0813346 A1 12/1997  
 EP 0974895 A2 1/2000  
 EP 1088463 A1 4/2001  
 EP 1128704 A1 8/2001  
 EP 1138173 A1 10/2001  
 EP 1244261 A2 9/2002  
 EP 1345370 A2 9/2003  
 EP 0926608 B1 3/2004  
 EP 1458209 A2 9/2004  
 EP 1473872 A2 11/2004  
 EP 1489808 A2 12/2004  
 EP 1507421 A1 2/2005  
 EP 1565024 A2 8/2005  
 EP 1720267 A1 11/2006  
 EP 1764942 A2 3/2007  
 GB 2322046 8/1998  
 GB 2395629 A 5/2004  
 JP 2084807 3/1990  
 JP 08116329 5/1996  
 JP 11308273 11/1999  
 JP H11341541 A 12/1999  
 JP 2000125343 A 4/2000  
 JP 2001507897 T 6/2001  
 JP 2001217830 A 8/2001  
 JP 2001237878 A 8/2001  
 JP 2001245355 A 9/2001  
 JP 2002111732 A 4/2002  
 JP 2002513527 A 5/2002  
 JP 2002165249 A 6/2002  
 JP 2002281069 A 9/2002  
 JP 2002281539 A 9/2002  
 JP 2002533030 T 10/2002  
 JP 2002537739 11/2002  
 JP 2003060685 A 2/2003  
 JP 2003111134 A 4/2003  
 JP 2003348007 5/2003  
 JP 2003304571 A 10/2003  
 JP 2003338833 A 11/2003  
 JP 2004007578 A 1/2004  
 JP 2004506358 T 2/2004  
 JP 2004104544 A 4/2004  
 JP 2004147228 5/2004  
 JP 2004187256 A 7/2004  
 JP 2004201289 A 7/2004  
 JP 2004297130 A 10/2004  
 JP 2004328637 A 11/2004  
 JP 2004328727 A 11/2004  
 JP 2005531173 T 10/2005  
 JP 2007527177 T 9/2007  
 JP 2008053889 A 3/2008  
 JP 4827994 B1 11/2011  
 KR 20040004918 A 1/2004  
 KR 20040105069 A 12/2004  
 KR 20050023194 A 3/2005  
 KR 20050065123 6/2005  
 KR 20050066287 A 6/2005  
 KR 20070031810 A 3/2007  
 RU 2117396 C1 8/1998  
 RU 2256299 C2 7/2005  
 RU 2292669 1/2007

RU 2294596 C2 2/2007  
 TW 200527930 8/2005  
 WO 9501706 A1 1/1995  
 WO WO-9627993 A1 9/1996  
 WO WO-9712475 A1 4/1997  
 WO 9804094 A1 1/1998  
 WO 9833288 7/1998  
 WO 9847302 10/1998  
 WO 9856140 A2 12/1998  
 WO 9905828 A1 2/1999  
 WO 9927718 6/1999  
 WO 9966748 A1 12/1999  
 WO 0041426 A1 7/2000  
 WO 0128160 A2 4/2001  
 WO 0158196 A1 8/2001  
 WO 0163947 8/2001  
 WO 0219746 A1 3/2002  
 WO 0243409 A2 5/2002  
 WO 02056551 A1 7/2002  
 WO 03007484 A2 1/2003  
 WO 03017582 2/2003  
 WO 03092316 A1 11/2003  
 WO 03098816 A2 11/2003  
 WO 03105516 A1 12/2003  
 WO 2004039022 A2 5/2004  
 WO 2004068739 A1 8/2004  
 WO 2004079949 A1 9/2004  
 WO 2004105272 A1 12/2004  
 WO 2004107638 A2 12/2004  
 WO 2004114695 A1 12/2004  
 WO 2005048629 A1 5/2005  
 WO 2005078966 A1 8/2005  
 WO 2005084146 A2 9/2005  
 WO 2005120183 A2 12/2005  
 WO 2006002676 A1 1/2006  
 WO WO-2006020105 A1 2/2006  
 WO 2006083131 A1 8/2006  
 WO 2008113373 A1 9/2008  
 WO 2008131401 A1 10/2008

**OTHER PUBLICATIONS**

3GPP TS 36.423, "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (EUTRAN); X2 Application Protocol (X2AP)", version 0.0.1, Release 8, year 2007, pp. 9.

"3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA) Radio Resource Control (RRC); Protocol specification (Release 8)" 3GPP Standard; 3GPP TS 36.331, 3rd Generation Partnership Project (3GPP), Mobile Competence Centre; 650, Route Des Lucioles ; F-06921 Sophia-Antipolis Cedex; France, No. V8.2.0, May 1, 2008, pp. 1-151, XP050377645.

3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA) Radio Resource Control (RRC); Protocol specification (Release 9), 3GPP Standard; 3GPP TS 36.331, 3rd Generation Partnership Project (3GPP), Mobile Competence Centre ; 650, Route Des Lucioles ; F-06921 Sophia-Antipolis Cedex ; France, No. V9.1.0, Jan. 7, 2010, pp. 1-221, XP050401822, [retrieved on Jan. 7, 2010]. Baker, F., IETF, "RSVP Management Information Base Using SMIPv2," Network Working Group, Request for Comments: 2206, pp. 1-64 (Sep. 1997).

Basic Knowledge of Communications Term of Switching HUB, Nov. 9, 2006, 2 pgs.

Berger, L., et al., "RSVP Extensions for IPSEC Data Flows," IETF, Network Working Group, Request for Comments: 2207, pp. 1-14 (Sep. 1997).

Berger, L., "RSVP Refresh Overhead Reduction Extensions," IETF Network Working Group, Request for Comments: 2961, pp. 1-34 (Apr. 2001).

Bos et al., "A Framework for End-to-End Perceived Quality of Service Negotiation", IETF Internal Draft, draft-bos-mmusic-sdpqos-framework-00.txt, Nov. 2001, pp. 1-22.

(56)

**References Cited****OTHER PUBLICATIONS**

- Braden, R., "Resource ReSerVation Protocol (RSVP)—Ver. 1, Message Processing Rules," IETF, Network Working Group, Request for Comments: 2209, pp. 1-25 (Sep. 1997).
- Braden, R., "Resource ReSerVation Protocol (RSVP)—Ver. 1 Functional Specification," IETF, Network Working Group, Request for Comments: 2205, pp. 1-112 (Sep. 1997).
- Camarillo, G., et al., "Integration of Resource Management and SIP," IETF Internet Draft, draft-ietf-sip-manyfolks-resource-04.ps, Feb. 25, 2002, pp. 1-18.
- Campbell, Andrew T. et al., "IP Micro-Mobility Protocols", Mobile Computing and Communications Review (MC2R), vol. 4, No. 4, pp. 45-53, (Oct. 2001).
- Co-pending U.S. Appl. No. 08/144,901, filed Oct. 28, 1993.
- Droms, R.: "Dynamic Host Configuration Protocol," IETF Standard, RFC 2131, Internet Engineering Task Force, IETF, CH, pp. 1-45, (Mar. 1997) XP015007915.
- Etri, "Source Specific Multicast (SSM) Explicit Multicast (Xcast)" pp. 1-27 (Jun. 28, 2001).
- Ho, Michael, "Integration AAA with Mobile IPv4", Internet Draft, pp. 1-59, Apr. 2002.
- Huawei, et al., "Clarification of definitions of HO failure cases", RAN3, 3GPP Draft; 36300\_CR0202\_(REL-9)\_R2-101906\_R3-100635, 3rd Generation Partnership Project (3GPP), Mobile Competence Centre ; 650, Route Des Lucioles ; F-06921 Sophia-Antipolis Cedex ; France, vol. RAN WG2, no. San Francisco, USA; 20100222, Mar. 4, 2010, XP050422194, 3 pgs. [retrieved on Mar. 4, 2010].
- Ian F.A., et al., "Mobility Management in Next-Generation Wireless Systems", Proceedings of the IEEE, IEEE, New York, us, vol. 87, No. 8, Aug. 1, 1999, XP011044241, ISSN: 0018-9219, pp. 1347-1384.
- International Search Report dated Feb. 22, 2007 for PCT/US2006/036580.
- Johnson, D., et al., IETF Mobile IP Working Group, "Mobility Support in IPv6,"; Feb. 26, 2003 Downloaded from <http://www.join.uni-muenster.de> on Dec. 29, 2004, pp. 1-169.
- Karagiannis, Georgios, "Mobile IP: State of the Art Report," Ericsson, No. 3/0362-FCP NB 102 88 UEN, pp. 1-63, (Jul. 13, 1999).
- Koodli, R. et al.: "Fast Handovers and Context Transfers in Mobile Networks" Computer Communication Review, ACM, New York, NY, US, vol. 31, No. 5, Oct. 1, 2001, pp. 37-47, XP001115324 ISSN: 0146-4833 abstract p. 2, right-hand column, last paragraph—p. 3, left-hand column, paragraph 3 p. 5, right-hand column, last paragraph—p. 7, right-hand column, last paragraph.
- Leon-Garcia, Alberto; "Communication Networks: Fundamental Concepts and Key Architectures" McGraw-Hill; 2nd Edition; Copyright 2004, pp. 44-52, 429-431.
- Li, Yalun et al. "Protocol Architecture for Universal Personal Computing," IEEE Journal on Selected Areas in Communications, IEEE Inc. New York, US, vol. 15, No. 8, Oct. 1, 1997, pp. 1467-1476, XP000721278 ISSN: 0733-8716.
- Loughney, J. et al. "Context Transfer Protocol (CXTP)" IETF Standard, Request for Comments: 4067, Internet Engineering Task Force, IETF, CH, Jul. 2005, XP015041932 ISSN: 0000-0003 pp. 1 to 33.
- Mankin, A., et al., "Resource ReSerVation Protocol (RSVP) Version 1, Applicability Statement: Some Guidelines on Deployment", IETF, Network Working Group, Request for Comments: 2208, pp. 1-6 (Sep. 1997).
- Marshall, W. et al. "Integration of Resource Management and SIP: SIP Extensions for Resource Management," IETF Internet Draft, draft-ietf-sip-manyfolks-resource-02.txt, Aug. 2001, pp. 1-28.
- Miorandi D., et al., "Analysis of master-slave protocols for real-time industrial communications over IEEE 802.11 WLANs" Industrial Informatics, 2004. Indin '04, 2nd IEEE International Conference on Berlin, Germany Jun. 24-26, 2004. Piscataway, NJ, USA IEEE, June 24, 2004, pp. 143-148, XP010782619, ISBN 0789385136, Para 3, point B.
- Mockapetris P., "Domain Names—Implementation and Specification", IETF RFC 1035, Nov. 1987.
- Moy, J., "OSPF Version 2", Network Working Group, Request for Comments: 2328, pp. 1-244 (Apr. 1998).
- "Network Layer Protocol," Jul. 13, 2002, chap. 6, pp. 1-35, URL: <http://www2.yamanashi-ken.ac.jp/~itoyo/lecture/network/network06/index06.htm>.
- Nortel: "Forward Hand-Off options", R2-071980, 3GPP TSG-RAN WG2 Meeting #58, Kobe, Japan, May 7-11, 2007, sections 2-3.
- Panasonic, "Necessity of forward handover", 3GPP Draft, R2-062146, 3rd Generation Partnership Project (3GPP), Mobile Competence Centre, 650, Route Des Lucioles, F-06921 Sophia-Antipolis Cedex, France, vol. RAN WG2, no. Tallinn, Aug. 23, 2006, XP050131764.
- Papalilo, D. et al. "Extending SIP for QoS Support", [www.coritel.it/publications/IP\\_download/papalilo-salsano-veltri.pdf](http://www.coritel.it/publications/IP_download/papalilo-salsano-veltri.pdf), Dec. 8, 2001, pp. 1-6.
- Perkins, C., "IP Mobility Support for IPv4", Nokia Research Center, Network Working Group, Request for Comments: 3220, Jan. 2002, downloaded from <http://www.ietf.org> on Dec. 29, 2004, pp. 1-92.
- Perkins, C., "IP Mobility Support", IBM, Network Working Group, Request for Comments: 2002, pp. 1-79 (Oct. 1996).
- Pollini, G P et al., "Trends in Handover Design" IEEE 34(3), pp. 82-90, Mar. 1, 1996, XP00557380.
- Rosenberg J et al:RFAC 3261: "SIP: Session Initiation Protocol" 20020600, Jun. 1, 2002, pp. 1-269, XP015009039.
- Schulzrinne et al., "Application-Layer Mobility Using SIP", 0-7803-7133 IEEE, pp. 29-36, Jan. 2000.
- Takako Mita, et al., A Proposal for Seamless QoS Support in Mobile Networks, Research Report of Information Processing Society 2004-MBL-29, Japan, Information Processing Society of Japan, May 13, 2004, vol. 2004, No. 44, pp. 129-134.
- "Terms for Use in Textbooks and Lectures on Distributed Computing," Feb. 13, 2005, URL: <http://web.archive.org/web/20050213090736/http://www.nuis.ac.jp/~nagai/lecture/dce.html>.
- Thulasi, A., et al., "IPv6 Prefix Delegation Using ICMPv6", Network Working Group, Hewlett-Packard, pp. 1-34, Apr. 2004.
- TIA/EIA/IS-707A.8 "Data Service Options for Spread Spectrum Systems: Radio Link Protocol Type 2" pp. 1-1:4:12 (Mar. 1999).
- Trossen, D. et al., "A Dynamic Protocol for Candidate Access-Router Discovery", 35 pgs., Mar. 14, 2003.
- Valko, A.G. et al.: "Cellular IP: A New Approach to Internet Host Mobility" Computer Communication Review, Association for Computing Machinery, New York, USvol. 29, No. 1, Jan. 1999, pp. 50-65, XP000823873 ISSN: 0146-4833, p. 56, Line 7-Line13.
- Wedlund et al: "Mobility Support Using SIP", Proc. of ACM/IEEE International Conference on Wireless and Mobile Multimedia (WoWMoM '99), Seattle, Washington, Aug. 1999.
- Written Opinion—PCT/US2006/036580, International Search Authority, European Patent Office, Jun. 20, 2006.
- Wroclawski, J., "The Use of RSVP with IETF Integrated Services," IETF, Network Working Group, Request for Comments: 2210, pp. 1-33 (Sep. 1997).
- Zhou, S., et al., "A Location Management Scheme for Mobility Support in Wireless IP Networks Using Session Initiation Protocol (SIP)", 1531-2216/01 IEEE, pp. 486-491, Oct. 2001.
- Zte, et al., "Handover Cause Report for Mobility Robustness Optimization", 3GPP Draft; R3-092982, 3rd Generation Partnership Project (3GPP), Mobile Competence Centre ; 650, Route Des Lucioles ; F-06921 Sophia-Antipolis Cedex ; France, no. Jeju; Nov. 9, 2009, XP050392455, 4 pgs. [retrieved on Nov. 19, 2009].
- Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2 (Release 9), 3GPP TS 36.300 V9.2.0, Dec. 2009, pp. 56-61, Retrieved from the internet: URL: [http://www.3gpp.org/ftp/Specs/archive/36\\_series/36.300/36300-920.zip](http://www.3gpp.org/ftp/Specs/archive/36_series/36.300/36300-920.zip).
- Qualcomm Europe, T-Mobile, "Network based solutions to inbound mobility in the presence of PCI confusion", 3GPP TSG-RAN WG3 #64, R3-091027, May 2008, pp. 1-4, Retrieved from the internet: URL: [http://www.3gpp.org/ftp/tsg\\_ran/WG3\\_lu/TSGR3\\_64/Docs/R3-091027.zip](http://www.3gpp.org/ftp/tsg_ran/WG3_lu/TSGR3_64/Docs/R3-091027.zip).
- Qualcomm Incorporated, "UE context fetch procedure stage 2", 3GPP TSG-RAN WG3 Meeting #67, R3-100893, Feb. 2010, pp. 1-4, Retrieved from the internet URL: [http://www.3gpp.org/ftp/tsg\\_ran/WG3\\_lu/TSGR3\\_67/Docs/R3-100893.zip](http://www.3gpp.org/ftp/tsg_ran/WG3_lu/TSGR3_67/Docs/R3-100893.zip).

(56)

**References Cited**

OTHER PUBLICATIONS

Aboba, et al. , "The Network Access Identifier, Request for Comments (RFC) 2486," 1999, 8.

Becker, et al., "RF Power Control in GSM Systems for Constant and Non Constant Envelope Modulation Schemes , ISCAS ," Proceedings of 2003 Initial Symptoms on Circuits and Systems, 2003, 3, III-602 to III-605.

"SIP: Session Initiation Protocol", IETF Network Group, Requests for Comments: 3261, (Jun. 2002), pp. 1-29.

Liang et al: "Nonlinear amplifier Effects in Communications Systems," IEEE Trans. On Microwave Theory and Techniques, vol. 47, No. 8, Aug. 1999, pp. 1461-1466.

NetworkWorking Group, IPv6 Prefix Delegation Using ICMPv6, pp. 1-33, Apr. 2004.

\* cited by examiner




FIG. 1










FIG. 2

**FIG. 3**

**FIG. 4**

**FIG. 5**

**FIG. 6**




FIG. 1




FIG. 8








FIG. 9





**FIG. 10**

**FIG. 11**

**FIG. 12**

**FIG. 13**

**FIG. 14**

**FIG. 15**




FIG. 16




FIG. 17






FIG. 18




FIG. 19

# STATE SYNCHRONIZATION OF ACCESS ROUTERS

## CROSS-REFERENCE

This application is a divisional of U.S. patent application Ser. No. 11/486,650, filed Jul. 14, 2006 and entitled "STATE SYNCHRONIZATION OF ACCESS ROUTERS" which claims priority to U.S. Provisional Patent Application Ser. No. 60/718,363, filed Sep. 19, 2005 and entitled "METHODS AND APPARATUS FOR THE UTILIZATION OF MOBILE NODES FOR STATE TRANSFER AS PART OF A HAND-OFF OPERATION"; and U.S. Provisional Patent Application Ser. No. 60/796,653, filed on May 1, 2006 and entitled "A METHOD AND APPARATUS FOR MOBILITY AWARE RESOURCE CONTROL" (Park). This application is also related to U.S. patent application Ser. No. 11/288,597, filed Nov. 29, 2005 and entitled "METHODS AND APPARATUS FOR THE UTILIZATION OF MOBILE NODES FOR STATE TRANSFER"; U.S. patent application Ser. No. 11/316,602, filed Dec. 22, 2005 and entitled "COMMUNICATIONS METHODS AND APPARATUS USING PHYSICAL ATTACHMENT POINT IDENTIFIERS"; U.S. patent application Ser. No. 11/316,376, filed Dec. 22, 2005 and entitled "COMMUNICATIONS METHODS AND APPARATUS USING PHYSICAL ATTACHMENT POINT IDENTIFIERS WHICH SUPPORT DUAL COMMUNICATIONS LINK"; U.S. patent application Ser. No. 11/316,603, filed Dec. 22, 2005 and entitled "METHOD AND APPARATUS FOR END NODE ASSISTED NEIGHBOR DISCOVERY"; and U.S. Pat. No. 6,862,446, filed Feb. 18, 2003 and entitled "METHODS AND APPARATUS FOR THE UTILIZATION OF CORE BASED NODES FOR STATE TRANSFER." This application is additionally related to the following co-filed patent applications: U.S. patent application Ser. No. 11/487,446, filed Jul. 14, 2006, entitled "PROVISION OF A MOVE INDICATION TO A RESOURCE REQUESTER" (Park, et al.); U.S. patent application Ser. No. 11/486,649, filed Jul. 14, 2006, entitled "PACKET ROUTING IN A WIRELESS COMMUNICATIONS ENVIRONMENT" (Park, et al.); U.S. patent application Ser. No. 11/486,654 filed Jul. 14, 2006, entitled "PROVISION OF QOS TREATMENT BASED UPON MULTIPLE REQUESTS" (Park, et al.); and U.S. patent application Ser. No. 11/486,655, filed Jul. 14, 2006, entitled "STATE SYNCHRONIZATION BETWEEN ACCESS ROUTERS" (Tsirtsis, et al.). The entireties of each of the aforementioned applications are incorporated herein by reference.

## BACKGROUND

### I. Field

The invention relates to communication systems and, more particularly, to synchronization between access routers in wireless communication systems.

### II. Background

Communication systems frequently include a number of network nodes through which end nodes (e.g., mobile devices) communicate. End nodes communicate with network nodes directly through connections that have been established with the network nodes. Such systems usually rely on the existence of a bidirectional communications link between an end node and an access node to support two-way communications. In such systems, the end node may not know the network layer address of a target destination network node but may be aware of information that it can receive over broadcast channels.

In some systems, end nodes are capable of maintaining multiple bidirectional communications links with different network nodes at substantially the same time. However, such systems typically require the end nodes to send messages intended for a specific network node, with which the end node has a connection, over the link that is directly connected to that specific network node. This approach might not be efficient in some situations especially for wireless link that can fluctuate in terms of quality (e.g., delay and loss characteristics). As a result, the link to the target destination network node may not be the best link available to the end node at the time a message is to be sent to the network node. Typically, this limitation is overcome by resorting to network layer communications that can be routed through multiple hops due to the use of network layer addresses (e.g., IP addresses). This approach of using network layer address may not be efficient especially when the messaging relates to link layer specific functions because network layer messages can be much larger than link layer messages in some systems. In addition, inefficient signaling is not suitable for communications over resource restricted air links.

Network nodes that are serving neighboring geographical cells are typically known to each other through a manual configuration. During such configuration, various parameters are configured in a network node corresponding to several of its neighbors. Such configuration is typically labor intensive and error prone due to human error and the fact that the network layout of a wireless networks often changed relevant to a gradual phased deployment of a wireless communications system.

In addition, the network nodes might not be aware of which of the other network nodes are serving the same end node. Thus, if there is a change in the state of the end node, it is unknown which, if any, of the other network nodes should have the state change information. This information regarding the state of the end node is important to maintain a consistent and reliable user experience.

Therefore, to overcome the aforementioned as well as other deficiencies, there is a need to communicate the state change information efficiently to maintain synchronization between network nodes.

## SUMMARY

The following presents a simplified summary in order to provide a basic understanding of some aspects of the disclosed embodiments. This summary is not an extensive overview and is intended to neither identify key or critical elements nor delineate the scope of such embodiments. Its sole purpose is to present some concepts of the described embodiments in a simplified form as a prelude to the more detailed description that is presented later.

In accordance with one or more embodiments and corresponding disclosure thereof various aspects are described in connection with updating access routers with wireless terminal state information. An access router can be at least a base station, an access point, a packet data serving node (PDSN), and/or a gateway general packet radio services (GPRS) support node. A wireless terminal state can be at least a terminal identification, a quality of service configuration, authorization parameters, and/or a timer associated with system use.

According to an embodiment is a method for state change synchronization with multi-party handshake. The method includes sending a first message to a first access router. The first message includes a first indicator for the first access router and at least a second indicator for at least a second

3

access router. The method also includes receiving an acknowledgment of the first message from the at least a second access router.

In accordance with another embodiment is an apparatus that facilitates state synchronization of access routers. The apparatus includes a processor that transmits a communication to a first access router. The communication can include a first address for a first access router and at least a second address for at least a second access router address. The apparatus also includes a receiver that receives a completion message from the second access router.

According to a further embodiment is an apparatus for state change synchronization. The apparatus includes a means for conveying a first message to a first access router. The first message includes a first address of the first router address and at least a second address of at least a second access router. The apparatus further includes a means for accepting at least a subset of the first message from the second access router.

According to another embodiment is a computer-readable medium having stored thereon computer-executable instructions for updating a multitude of access routers with state change information. The instructions include communicating a message to a first access router. The message includes a state change of a wireless terminal, an address of the first access router, and at least a second address of at least a second access router. The instructions further include receiving an acknowledgment of the message from the second access router.

Still another embodiment is a processor that executes computer-executable instructions for communicating a state change to a multitude of access routers. The computer-executable instructions include conveying a message to a first access router. The message includes a first address of the first access router, at least a second address of at least a second access router, and a return address for a wireless device. The computer-executable instructions further include acquiring at least a subset of the message from the second access router.

Another embodiment includes a method for updating a multitude of access routers with terminal state information. The method includes receiving at a first access router a message having an address for a second access router and an address for at least a third access router. The method further includes routing at least a subset of the message to one of the second and the third access router.

Still another embodiment is an apparatus that facilitates performance consistency of a wireless user device. The apparatus includes a processor that accepts a message from a wireless device. The message includes an indicator for a first access router, an indicator for a second access router, and an indicator for at least a third access router. A memory that stores information related to a state change of the wireless device is included in the apparatus. Also included is a transmitter that transmits at least a subset of the message and the state change to the second access router.

In accordance with another embodiment is an apparatus for synchronizing access routers with wireless terminal state change information. Included in the apparatus is a means for acquiring a message from a wireless terminal and a means for communicating at least a subset of the message to the second access router. The message can include an address for the first access router, an address for a second access router, an address for at least a third access router, and an address for the wireless terminal.

According to another embodiment is a computer-readable medium having stored thereon computer-executable instructions for state change synchronization between a multitude of access routers utilizing multiparty handshake. The instructions include accepting at a first access router a communication

4

for a wireless terminal and transmitting at least a subset of the communication to a second access router. The communication can include a wireless terminal address, an indicator for the first access router, an indicator for the second access router, and an indicator for at least a third access router.

In accordance with a further embodiment is a processor that executes computer-executable instructions for state change synchronization. The instructions include receiving a message that includes a first address of a first access router, a second address of a second access router, and at least a third address of at least a third access router. The instructions also include conveying at least a subset of the message to the second access router.

According to a further embodiment is a method for uniformly updating a multitude of access routers with wireless terminal state change information. The method includes receiving a first message at a first access router, the message including a first indicator for the first access router and at least a second indicator for at least a second access router and a state of a wireless terminal. The method further includes sending at least a subset of the first message to the second access router.

Still another embodiment is an apparatus that facilitates state information synchronization between access routers. The apparatus includes a processor that receives a communication that includes a state of a wireless device, an address for a first access router, and an address for at least a second access router. Also included in the apparatus is a memory that stores information related to the state of the wireless device and a transmitter that transmits at least a portion of the communication to the second access router.

In accordance with another embodiment is an apparatus that facilitates performance consistency of a wireless device. The apparatus includes a means for accepting at a first access router a message from a second access router and a means for conveying at least a subset of the message to a third access router. The message includes a changed state of a wireless device, an address for the first access router, and an address for at least the third access router.

Still another embodiment is a computer-readable medium having stored thereon computer-executable instructions for state synchronization among access routers. The instructions include acquiring at a first access router a communication. Included in the communication is an identification of the first access router, an identification of at least a second access router, and a state of a wireless device. The instructions also include transmitting at least a subset of the communication to the second access router.

According to another embodiment is a processor that executes computer-executable instructions for synchronizing wireless terminal state changes. The instructions include receiving at a first access router a message that includes a state change for a wireless terminal and transmitting at least a subset of the message to at least a second access router. The message includes an address for the first access router and an address for at least a second access router.

In accordance with another embodiment is a method for updating an access router with wireless terminal state information. The method includes receiving a first message at a first access router. The message includes a first access router indicator and at least a state of a wireless terminal. The method further includes sending an acknowledgment of the first message to the wireless terminal.

Still another embodiment is an apparatus that synchronizes an access router with wireless device state information. The apparatus includes a processor that receives a message that includes a wireless device state information. Also included in

5

the apparatus is a memory that stores the wireless device information in a retrievable format. A transmitter that transmits at least a subset of the message to the wireless device as an acknowledgment of successful receipt of the first message is also included in the apparatus.

In accordance with another embodiment is an apparatus that facilitates synchronization of wireless state information at an access router. The apparatus include a means for accepting at a first access router a communication from a second access router. Also included is a means for transmitting an acknowledgment of the communication to the wireless device. The message can include an address of the first access router and a state of a wireless device.

Yet another embodiment is a computer-readable medium having stored thereon computer-executable instructions for providing a uniform wireless terminal user experience. The instructions include receiving a communication that includes a first access router address and a state change for a wireless device. The instructions further include conveying at least a subset of the message to the wireless device.

A further embodiment includes a processor that executes computer-executable instructions for state synchronization of an access router. The instructions include accepting at a first access router a message and outputting to a wireless device at least a subset of the message. The message can include an address of the first access router and a changed state for the wireless device.

To the accomplishment of the foregoing and related ends, one or more embodiments comprise the features hereinafter fully described and particularly pointed out in the claims. The following description and the annexed drawings set forth in detail certain illustrative aspects and are indicative of but a few of the various ways in which the principles of the embodiments may be employed. Other advantages and novel features will become apparent from the following detailed description when considered in conjunction with the drawings and the disclosed embodiments are intended to include all such aspects and their equivalents.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a wireless communications system for stay change synchronization with multi-party handshake.

FIG. 2 illustrates an embodiment of a wireless communications system for state change synchronization with multi-party handshake at the system core.

FIG. 3 illustrates a methodology for communicating access router information for synchronization of state information.

FIG. 4 illustrates a methodology for receiving a state change notification and conveying at least a subset of the state change information.

FIG. 5 illustrates a methodology for routing terminal state information for synchronization between access routers.

FIG. 6 illustrates a methodology for synchronizing a terminal state and providing an acknowledgment upon successful receipt of the state information.

FIG. 7 illustrates a wireless communications system for synchronization of state information between multiple access routers.

FIG. 8 illustrates an embodiment of a wireless communications system for synchronization of state information between multiple access routers at the system core.

FIG. 9 illustrates a methodology for communicating state information for synchronization of access routers.

FIG. 10 illustrates a methodology for state synchronization of multiple access routers with minimal communication from a wireless terminal.

6

FIG. 11 illustrates a wireless device that communicates with an access router in accordance with the various embodiments.

FIG. 12 illustrates an access router that facilitates state synchronization.

FIG. 13 illustrates a block diagram of an apparatus for state change synchronization.

FIG. 14 illustrates a block diagram of an apparatus for synchronizing access routers with wireless terminal state change information.

FIG. 15 illustrates a block diagram of an apparatus that facilitates performance consistency of a wireless device.

FIG. 16 illustrates a block diagram of an apparatus that facilitates synchronization of wireless state information at an access router.

FIG. 17 illustrates a network diagram of an exemplary communications system implemented in accordance with the various embodiments.

FIG. 18 illustrates an exemplary base station implemented in accordance with the embodiments presented herein.

FIG. 19 illustrates an exemplary wireless terminal implemented in accordance with various embodiments presented herein.

#### DETAILED DESCRIPTION

Various embodiments are now described with reference to the drawings. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of one or more aspects. It may be evident, however, that such embodiment(s) may be practiced without these specific details. In other instances, well-known structures and devices are shown in block diagram form in order to facilitate describing these embodiments.

As used in this application, the terms “component,” “module,” “system,” and the like are intended to refer to a computer-related entity, either hardware, firmware, a combination of hardware and software, software, or software in execution. For example, a component may be, but is not limited to being, a process running on a processor, a processor, an object, an executable, a thread of execution, a program, and/or a computer. By way of illustration, both an application running on a computing device and the computing device can be a component. One or more components can reside within a process and/or thread of execution and a component may be localized on one computer and/or distributed between two or more computers. In addition, these components can execute from various computer readable media having various data structures stored thereon. The components may communicate by way of local and/or remote processes such as in accordance with a signal having one or more data packets (e.g., data from one component interacting with another component in a local system, distributed system, and/or across a network such as the Internet with other systems by way of the signal).

Furthermore, various embodiments are described herein in connection with a user device. A user device can also be called a system, a subscriber unit, subscriber station, mobile station, mobile device, remote station, access point, base station, remote terminal, access terminal, handset, host, user terminal, terminal, user agent, wireless terminal, wireless device, or user equipment. A user device can be a cellular telephone, a cordless telephone, a Session Initiation Protocol (SIP) phone, a wireless local loop (WLL) station, a Personal Digital Assistant (PDA), a handheld device having wireless connection capability, or other processing device(s) connected to a wireless modem.

Moreover, various aspects or features described herein may be implemented as a method, apparatus, or article of manufacture using standard programming and/or engineering techniques. The term "article of manufacture" as used herein is intended to encompass a computer program accessible from any computer readable device, carrier, or media. For example, computer readable media can include but are not limited to magnetic storage devices (e.g., hard disk, floppy disk, magnetic strips . . . ), optical disks (e.g., compact disk (CD), digital versatile disk (DVD) . . . ), smart cards, and flash memory devices (e.g., card, stick, key drive . . . ).

Various embodiments will be presented in terms of systems that may include a number of device, components, modules, and the like. It is to be understood and appreciated that the various systems may include additional devices, components, modules, etc. and/or may not include all of the devices, components, modules etc. discussed in connection with the figures. A combination of these approaches may also be used.

With reference now to the drawings, FIG. 1 illustrates a wireless communications system **100** for state change synchronization with multi-party handshake. A wireless terminal **102** can be capable of communicating with multiple access routers at substantially the same time (e.g., multiple links to direct access routers) without the need for a handoff (e.g., wireless device is stable) between access routers. As illustrated, wireless terminal **102** can communicate with a first access router (Access Router<sub>1</sub>) **104**, a second access router (Access Router<sub>2</sub>) **106**, and at least a third access router (Access Router<sub>N</sub>) **108**, wherein N can be any integer equal to or greater than one. An access router is a device with built-in routing-protocol support and can be a base station, an access point (e.g., IEEE 802.11 access point, IEEE 802.11 (WiMAX) access point, IEEE 802.20 access point), a packet data serving node (PDSN), a gateway general packet radio services (GPRS) support node, FLASH OFDM, or some other terminology. It should be understood that while only one wireless terminal **102** is illustrated, multiple wireless terminals could be in communication with access routers **104**, **106**, and **108** at substantially the same time.

Generally, wireless terminal **102** is in an active state of operation (including a hold state of operation) with one or more of the access router **104**, **106**, or **108** at any given time. The link with each access router **104**, **106**, or **108** is independent. During the active state of operation communication with the access router, a state of wireless terminal **102** might change. For example, when a voice call is set up through an access router, there is a communication through the access router and a new piece of state (e.g., changes in the quality of service configuration to accommodate the voice call) is created. To maintain that voice call, each access router with which the wireless terminal communicates though should have information regarding the new piece of state. Therefore, the state should be replicated in the other access routers, such as through a dynamic synchronization.

Either or both wireless terminal **102** and access router **104**, **106**, **108** may be aware of the change in the state of the wireless terminal and can notify each other of such a state change. Such a change may occur based on the type of communication to be transmitted (e.g., voice, imagery, text, and the like), on the amount of system **100** traffic, or some other condition that affects the communication link between wireless terminal **102** and access routers **104**, **106**, and **108**. The state of wireless terminal **102** might also change due to an external event (e.g., a server changing a time), even when wireless terminal **102** is in a hold or sleep state. Examples of a state of wireless terminal **102** include but are not limited to a terminal identification, security parameters (e.g., keys), a

quality of service (QoS) configuration, authorization parameters, timers associated with system use, a condition of a link, etc. The terminal identification provides information as to which wireless terminal **102** the communication applies.

Security parameters provide information as to what keys are used for one of authentication, encryption, and derivation of other keys between the access router and the wireless terminal. QoS configuration for wireless terminal **102** allows traffic to be handled in higher or lower priority, more or less probability of delay, and more or less probability of loss. The authorization parameters can include information regarding actions a user of a particular wireless device can or cannot perform. The timers associated with system **100** use my indicate the expiration of a time after which wireless terminal **102** is no longer authorized to use the system, or vice versa. There is a multitude of other states that access router(s) **104**, **106**, and **108** may hold for a wireless terminal **102**, and which should be synchronized among access routers **104**, **106**, **108** to provide a consistent user experience.

Other exemplary states include, but are not limited to the following: HaAddress, HoAddress, MIPLifetime, HomeNAI, TempNAI, LocationUpdateInterval, PagingCycle, MSK, MSKLife. HaAddress is an IP Address of the HA used by the subscriber. HoAddress is an IP Address assigned to the subscriber. MIPLifetime is the Lifetime of the HoAddress. HomeNAI is the Home Network Access Identifier and is the permanent and globally unique identifier of the subscriber. TempNAI is a Temporary Network Access Identifier and is a locally unique identifier assigned to the subscriber. LocationUpdateInterval is the maximum interval in which the terminal must send location update messages when it is in a sleep state. PagingCycle is the frequency in which the terminal must check the paging channel for pages. MSK is a Master Session Key, which is a Key derived from the authentication phase during access. It is utilized to derive airlink keys for encryption/authentication. MSKLife is the Lifetime of the MSK.

At substantially the same time as the state of wireless terminal **102** changes, a new piece of the state (shown as dot **110**) is created in access router **104** aware of the state change. It should be understood that while the following discussion relates to access router **104** being the base station that is aware of the state change, any access router can be aware of the change and the following applies equally to any access router **104**, **106**, and **108**. Access router **104** can send an optional message **112** to wireless terminal **102** indicating a state change. In accordance with some embodiments, wireless terminal **102** may be aware of the state change and does not need a message from access router **104**. In some embodiments, access router **104** may not be aware of the state change, thus, there is no message sent to wireless terminal **102**, however, wireless terminal **102** should notify access router **104** of the state change and the change **110** is created in access router **104**.

Wireless terminal **102** can forward a message **114** to any access router **104**, **106**, or **108** indicating that there is a state change. If wireless terminal **102** sends the message to access router **104** aware of the state change, the message does not have to provide the state change information. If, however, wireless terminal **102** sends a notification of a state change in message to a different access router **106** or **108**, as illustrated, the message should contain the state change information in order for the other access routers in communication with wireless terminal **102** to have a new piece of the state (illustrated as dots **116** and **118**).

Message **114** sent by wireless terminal **102** can include a listing of access routers **104**, **106**, **108** to which wireless terminal **102** can communicate without a handoff occurring.

The link between wireless terminal **102** and the access routers to which message **114** is not sent does not have to be an active state of operation (e.g., hold, sleep). In accordance with some embodiments, message **114** includes an address of wireless terminal **102**. Message **114** can include an indicator of the access router(s), which can be a network address or IP address, a physical layer address, a connection identification (CID), a lower layer address or link layer address, a Logical Link Control (LLC) identification, or another means of identifying or distinguishing the access routers.

Access router **108** at substantially the same time as receiving message **114**, identifies itself as one of the access routers included in message **114**. If state information is included in the message, and access router **108** is not aware of the state information, access router **108** can store the information **116** in a storage medium. The information should be retained in a readily accessible manner to allow for identification and retrieval of the state information when a subsequent communication is received from (or intended for) wireless terminal **102**. Access router **108** can mark its address as having received the message or simply remove its address or identifier from the message in accordance with some embodiments prior to routing the remaining portion of the message to another access router. Marking the address, rather than removing the address allows other access routers to know which access routers in the list have already received and synchronized the state information. In accordance with some embodiments, the message is sent to access router **104** that notified wireless terminal **102** of the state change, and therefore, message (sent to access router **104**) does not include the state information. In such embodiments, access router **104** can append the state information to the message (prior to forwarding to another access router identified in message.

The next access router **106** stores the state change information **118** in a retrievable format. An identification of access router **106** can be marked as synchronized or removed from the message and the subset of the message forwarded **122** to the next access router **104**. Each access router performs a similar function until the last access router in the list receives the information. This last access router, after recording the state change information, forwards the message or an acknowledgment (ACK) **120** to wireless terminal **102**. ACK **120** can be message **114**, a subset of message **114**, or another communication notifying wireless device **102** that the access routers identified in message **114** have been updated with the state information. In such a manner, information is exchanged between access routers **104**, **106**, and **108**, and an acknowledgment **120** sent to wireless terminal **102** without the need for wireless terminal **102** to communicate individually with each access router **104**, **106**, and **108**.

FIG. 2 illustrates an embodiment of a wireless communication system **200** for state change synchronization with multi-party handshake at the system core. It should be understood that while the various embodiments shown and described herein refer to a state change, the disclosed techniques can work equally well in other situations. An example of such a situation includes when a wireless device is new to a communications system and, thus, access router(s) need to be synchronized to communicate with wireless device. Another situation occurs when a new access router entering the communications system and should be synchronized with the wireless terminal state information.

A wireless terminal **202** can communicate with a first access router (Access Router<sub>1</sub>) **204**, a second access router (Access Router<sub>2</sub>) **206**, and at least a third access router (Access Router<sub>N</sub>) **208**, wherein N can be any integer equal to or greater than one. Each access router **204**, **206**, **208** can operate

in a respective geographic area or cell, depicted as dotted lines and labeled "Cell A" **210**, "Cell B" **212**, and "Cell Z" **214**, wherein Z is an integer greater than or equal to one. Each cell **210**, **212**, **214** can have one or more base stations. For example, Cell A **210** includes Base Station<sub>1A</sub> **216** and Base Station<sub>MA</sub> **218**, Cell B **212** includes Base Station<sub>1B</sub> **220** and Base Station<sub>MB</sub> **222**, and Cell Z **204** includes Base Station<sub>1Z</sub> **224** and Base Station<sub>MZ</sub> **226**, wherein M is an integer greater than or equal to zero. Each base station **216-226** communicates with a respective access router **204**, **206**, or **208**, through a network **228**, **230**, **232**.

The access routers **204**, **206**, **208** contain the terminal state information and no state information is maintained at the base station **216-226** level. Since wireless terminal **202** can communicate with devices in any cell **210**, **212**, and **214**, synchronization of terminal state information should be synchronized among access routers **204**, **206**, **208** to maintain a consistent user experience. The transfer of terminal state information is similar to that shown and described with reference to the above figure.

Wireless terminal **202** at substantially the same time as receiving notification of a state change (either from an access router (shown as optional communication **234**, or based on its own knowledge), notifies **236** an access router **208** of the state change and includes an indicator for the access routers to which the wireless terminal **202** is connected. Although the communication to access router **208** is illustrated as traversing through base station **224**, the communication can be through either base station **224** or **226**. Access router **208**, maintains the state change **238** in a retrievable format. In accordance with some embodiments, access router **208** can mark or otherwise identify its address as being synchronized with the information or remove its own address from the message, and forward the remaining subset of the message **240** to the next access router **206** identified in message **236**. The terminal state **242** is recorded in access router **206** and a message **244** forwards to the next identified access router **204**. Message **244** can be a subset of message **240** or **236** with the address of access router **206** marked or removed. This process continues until the state change information is received at the last access router **204** identified in message **236**. The last access router **204** records the state change **246** and forwards an ACK **248** to wireless terminal **202**, which can be the last address included in the message **236**. It should be understood that while communication with wireless terminal **202** has been illustrated as flowing through a particular base station, the communication can be transferred through any base station.

FIG. 3 illustrates a methodology **300** for communicating access router information for synchronization of state information. While, for purposes of simplicity of explanation, the methodologies are shown and described as a series of blocks, it is to be understood that the disclosed embodiments are not limited by the number or order of blocks, as some blocks may occur in different orders and/or concurrently with other blocks than what is depicted and described herein. Moreover, not all illustrated blocks may be required to implement the described methodologies. A methodology could alternatively be represented as a series of interrelated states or events, such as in a state diagram. It is to be appreciated that the functionality associated with the blocks may be implemented by software, hardware, a combination thereof or any other suitable means device, system, process, component). Additionally, it should be appreciated that the methodologies disclosed throughout this specification are capable of being stored on an article of manufacture to facilitate transporting and transferring such methodologies to various devices.

11

Methodology **300** begins at **302** where a state change notification is received at, for example, a wireless terminal. The state change can relate to how the network performs with respect to the wireless terminal, a condition of a link, a quality of service configuration, an authorization parameter, a terminal identification, timers associated with system use, or other information. The state change notification can be received from an access router that has an active link with the wireless terminal. In some embodiments, the wireless terminal can receive the state change notification from a processor or other device internal to the wireless terminal that detects or processes the state change. Thus, receiving the notification from a source external to the wireless device is optional.

At **304**, a message is sent to an access router. The message can be sent over an Internet protocol, in an application that is currently running, or through other communication means. The message can include a listing of at least two access routers to which wireless terminal is linked and to which wireless terminal can communicate without the need for a handoff. The listing of access routers can include a specific route that the message should take through the access routers (e.g., source-based routing). In some embodiment, the listing includes the access routers but not routing information (e.g., the routing among access routers can take any path). The listing of access routers can include an indicator, such as an address or other means of identifying the access routers. If the message is sent to an access router that sent a notification, at **302**, the message may not include the state change information. However, if the notification received, at **302**, was not from an access router, or if the message, sent at **304**, is to a different access router than the one that sent a notification, at **302**, the message should include the state change information. It is to be understood that the wireless terminal may not necessarily understand or process the state change, but should know that there is a state change in order to convey the appropriate message at **304**. Included in the message can be a resource reservation protocol. In some embodiments, the message can include an encryption key and/or timers associated with an encryption key.

A determination is made, at **306**, whether an acknowledgment (ACK) has been received from an access router different from the access router to which the message was sent, at **304**, such as the list access router in the message. If an ACK has been received ("YES"), it indicates that the relevant access routers have been updated with the state change information. If an ACK has not been received ("NO") a determination is made, at **308**, whether a predetermined period has elapsed. The period can be measured utilizing any means (e.g., time, algorithm). If the period has not elapsed ("NO"), the method continues, at **306**, for a determination whether an ACK has been received. The ACK may be an actual acknowledgment of the message or it may be a subset of the message sent, at **304**. If the period has elapsed ("YES") (e.g., timer has timed out), it indicates that there has been a communication failure and the method continues at **304**, where another message is sent to an access router. The message may include a routing different from the original routing, if a routing was provided. In some embodiments, the message may include a request for an ACK from each access router, rather than one ACK from the last access router that receives the message. An ACK, from each access router would provide an indication of which access router has experienced a communication failure. The communication failure can be the result of a multitude of conditions including an incorrect address, a failure at one or more access router, or another condition. It should be understood the method can proceed from **308** to **304** or **306** any number of times, until an ACK is received.

12

FIG. **4** illustrates a methodology **400** for receiving a state change notification and conveying at least a subset of the state change information. At **402**, an optional notification of a state change is sent to a wireless device. The notification can be sent if the wireless device is not aware that there has been a state change (e.g., no message has been received from the wireless device). It should be understood that in accordance with some embodiments, there is no notification sent at **402** and the method begins at **404**, where a message is received from the wireless device. This can occur if the wireless device is aware of the state change.

The message received, at **404**, can include information regarding the state change. In accordance with some embodiments, the information regarding the state change can be added to the message, such as by an access router that sent the initial notification, at **402**. Thus, in some embodiments, the wireless terminal is not aware of the state that changed, only that there was a change. The message received, at **404**, should include an indicator for at least two more access routers. The indicator can be, for example an IP address, a CID or physical layer address, a LLC identifier or link layer address, a network address, or the like.

The state change information in the received message is stored in the access router receiving the message. The indicator for the access router can be marked as having received and synchronized with the information or the indicator for the access router can be removed from the message and, at **406**, the marked or remaining portion of the message can be routed to one of the other access routers. The marked or remaining portion of the message should include the identifier for the other access routers and the state change information. In accordance with some embodiments, an ACK is sent to the wireless terminal at substantially the same time as the message is forwarded to one of the other access routers identified in the message.

FIG. **5** illustrates a methodology **500** for routing terminal state information for synchronization between access routers. At **502**, a message that includes a state of a wireless terminal is received. This message can be received from an access router that directly received a message from the wireless terminal. In some embodiments, the message is received from an access router that received the information from another access router, rather than directly from the wireless terminal. The message can include an indicator for the access router that received the message, at **502**, and at least one other access router to which the information should be communicated. The state of the wireless terminal can be stored in a storage medium or memory and should be in a readily retrievable format.

At **504**, an access router is identified through the indicator included in the message and can be any access router included in the message or it can be the next access router included in the message (e.g., designated routing of the message). The indicator of the access router can be marked as synchronized with the message information or removed from the message prior to the message being sent to the identified next access router. In such a manner, the next access router receives the state change information as well as the remaining access routers that should receive the state change information and, in some embodiments, can receive information regarding access routers that have already been updated with the information. Thus, the message sent, at **506**, includes only a portion or subset of the originally received message. In some embodiments, the next access router contains a message that includes the access routers that have already received the information.



13

FIG. 6 illustrates a methodology 600 for synchronizing a terminal state and providing an acknowledgment upon successful receipt of the state information. The method 600 starts, at 602, when a message is received at an access router from another access router. The message can include an indicator of the access router receiving the message and a state of a wireless terminal. The state of the wireless terminal is retained by the access router and, at 604, a determination is made whether there is at least another access router indicator (e.g., address) included in the message.

If there is another access router indicator in the message ("YES"), it indicates that other access routers still need to be synchronized with the wireless terminal state information. The message is forwarded to the next access router, at 606, wherein the indicator of the current access router can be marked as having been synchronized or simply removed prior to forwarding the message. If there is no other access router indicated in the message ("NO"), an acknowledgment (ACK) is sent to the wireless terminal, at 608. In accordance with some embodiments, the ACK is the state of the wireless terminal. For example, the message can include indicators for the access routers and an indicator for the wireless terminal. The routing of the message would traverse the access routers and then be routed to the wireless terminal. The wireless terminal, upon receiving the state information confirms that this state information was already sent to its access routers, and thus, infers that there is state synchronization between its access routers. Thus, the ACK does not necessarily have to indicate that the message has been successfully received by each access router.

FIG. 7 illustrates a wireless communications system 700 for synchronization of state information between multiple access routers. System 700 includes a wireless terminal 702 capable of communicating with multiple access routers at substantially the same time without the need for a handoff between access routers. As illustrated, wireless terminal 702 can communicate with a first access router (Access Router<sub>1</sub>) 704, a second access router (Access Router<sub>2</sub>) 706, and at least a third access router (Access Router<sub>N</sub>) 708, wherein N is an integer equal to or greater than one.

If an access router 704, 706, or 708 detects a state change of wireless terminal 702, the access router can send a notification to wireless terminal 702, at 710. However, in some embodiments, wireless terminal 702 is aware of the state change and does not need notification 710 from access router 704. It should be understood that while access router 704 is illustrated as notifying wireless terminal 702 and/or receiving a message from wireless terminal 702, such notification and/or receipt can be performed by the other access routers 706 and/or 708.

Wireless terminal 702 can send a message, at 712, to access router 704. The message can include the changed state information and a listing of other access routers to which wireless terminal 702 communicates. If the message does not include the state change information, the message 712 should be sent to the access router 704 aware of the change (e.g., the access router that notified wireless terminal that there was a state change). Wireless terminal 702 does not need to know what state changed, only that there was a state change. In some embodiments, the message can include an encryption key and/or timers associated with an encryption key. Included in the message can be a resource reservation protocol.

At substantially the same time as receiving the message 712, access router 704 retains information 714 regarding the state. Access router also identifies the access routers that should receive the state information and sends an individual communication 716 and 718 to each identified access router

14

706 and 708. Information 720 and 722 regarding the state is retained by each access router 706 and 708. For example, access router 704 can receive a message from wireless terminal 702 indicating a state change and a listing of three access routers (704, 706, and 708). If access router 704 received the message from wireless terminal, access router 704 identifies access routers 706 and 708 as those access routers that should receive the state information. Thus, access router 704 would send a message that includes the state change information to access router 706 and a second message that includes the state change information to access router 708. The message sent to routers 706 and 708 does not have to include specific access router information.

In some embodiments, access router 704 receives a confirmation or acknowledgment 724, 726 from access router 706 and access router 708. Access router 704 can utilize acknowledgments 724, 726 to define when to send an acknowledgment (ACK) 716 to wireless terminal 702 after all access routers receive and synchronize the terminal state information. If an ACK is not received at wireless terminal 702 before expiration of a pre-determined interval, a subsequent message may be sent to the same or different access router 704. The expiration of the pre-determined interval indicates a communication failure at one or more access router, and therefore, the access routers may not have been synchronized with the terminal state information. However, in accordance with other embodiments, an ACK 716 is not sent to wireless terminal 702.

FIG. 8 illustrates another embodiment of a wireless communications system 800 for synchronization of state information between multiple access routers at the system core. System 800 includes a wireless terminal 802 that can communicate within one or more geographic cells, labeled Cell A 804, Cell B 806, and Cell Z 808. Each cell 804, 806, 808 can have one or more base stations. For example, Cell A 804 includes Base Station<sub>1A</sub> 810 and Base Station<sub>VA</sub> 12, Cell B 806 includes Base Station<sub>1B</sub> 814 and Base Station<sub>VB</sub> 816, and Cell Z 808 includes Base Station<sub>1Z</sub> 818 and Base Station<sub>VZ</sub> 820, wherein V is an integer greater than or equal to zero.

The base stations 810-820 communicate through respective wireless networks 822, 824, and 826 to respective access routers 828, 830, and 832 that are located at the system 800 core. In order to provide a consistent user experience, each access router 828, 830, and 832 should include a replicate of a state of the wireless terminal (e.g., synchronized with respect to the state). When a state changes, wireless terminal 802 may be aware of the change and automatically send a message 834 an access router, such as access router 830 through one of its base stations, such as base station 814. It should be understood that the message can be sent to any access router 828, 830, or 832 through one of its respective base stations 810-820.

In some embodiments, wireless terminal 802 is not aware of the state change and, therefore, receives a notification 836 that a state has changed from an access router through a base station, illustrated as base station 818. If wireless terminal 802 sends message 834 to an access router (through its respective base station) that sent notification 836, message 834 does not need to include the state change. If however, as illustrated, message 834 is sent to access router that did not send notification 836, the message 834 should include the state change information. Message 834 should contain a listing of access routers to which wireless terminal 802 can be in communication without handoff (e.g., access routers 828, 830, and 832).

Message 834 is relayed to access router 830 and the state change 838 is retained by access router 830 in a retrievable

15

format. Access router **830** can identify those access routers **828** and **832** that should receive the state change information, base on the information contained in message **834** and can forward at least a portion of the message **834** containing the state change information to these identified access routers **828** and **832**, as illustrated at **840** and **842**. At substantially the same time as receiving the messages **840** and **842**, each access router **828** and **832** stores a portion of the state change information **844** and **846**.

In some embodiments, each access router **828** and **832** sends an acknowledgment **848**, **850** to access terminal **830** upon successful receipt of the state change information sent in messages **840** and **842**. Access router **830** can send an acknowledgment **852** to wireless terminal **802** through base station **814** (or a different base station) upon receipt of the acknowledgment **848**, **850** from each access router **828** and **832** or at substantially the same time as sending each access router **828** and **832** a portion of the message. In accordance with some embodiments, wireless terminal **802** does not receive an acknowledgment **852**.

With reference now to FIG. 9, illustrated is a methodology **900** for communicating state information for synchronization of access routers. The method **900** starts at **902** where a notification is received indicating a state change. This notification can be received from an access router having an active link with a wireless terminal. In accordance with some embodiments, the wireless terminal is aware of a state change a notification is not sent from an access router. In such embodiments, method **900** starts, at **904**, where a message is sent to an access router, the message includes an indicator for at least two other access routers that communicate with wireless terminal. If wireless terminal received a notification of the state change and the message is sent to the access router that notified wireless terminal, the message does not need to include the state change. If, however, the wireless terminal did not receive a notification or if the message is sent to an access router different from the access router that sent the notification, the message should include information regarding the state that changed.

The method **900** continues, at **906**, where a determination is made whether an acknowledgment is received. If the acknowledgment is received ("YES"), the method ends. If an acknowledgment is not received ("NO"), a determination is made, at **908**, whether a pre-determined interval has expired. Such a pre-determined interval can take into account the amount of time needed to communicate with the various access routers to which wireless terminal has a link. The pre-determined interval can take into account the number of access routers as well as the number of wireless terminals serviced by such access routers. The pre-determined interval can also consider various other parameters including a communication speed, historical information regarding the response time for an acknowledgment, as well as other factors. It should be understood that in accordance with some embodiments, an acknowledgment is not received, thus, the method does not track an expiration of a pre-determined interval.

If the pre-determined interval has not expired ("NO"), the method continues at **906** with a determination whether an acknowledgment is received. If the pre-determined interval has expired ("YES") a subsequent message can be sent to the same or a different access router, at **904**. Expiration of the pre-defined interval can indicate a communication failure or other failure in the network, including defective access routers, overloaded access routers, access routers removed from the network, or other network scenarios. It should be understood that returning to **904** and/or **906** can be continuous, such

16

that any number of waiting periods can be entered or subsequent messages can be sent until an acknowledgment is received, in accordance with those embodiments that utilize an acknowledgment.

Turning now to FIG. 10, illustrated is a methodology **1000** for state synchronization of multiple access routers with minimal communication from a wireless terminal. At **1002**, an optional notification of a state change is sent to a wireless terminal. Such a notification can include information regarding the state change or a generic state change notification (e.g., a notification that a state changed but not the specifics of the state change). For those embodiments in which a state change notification is not sent to a wireless terminal, the method **1000** begins at **1004**, where a message is received from a wireless terminal.

The message received at **1004** should include an address for at least two other access routers with which wireless terminal has a communication link. The message received can also include the state change information if the access router receiving the message did not send the wireless terminal a state change notification. The access router that received the message identifies the other terminals that should receive the state information for synchronization in order to provide the user of the wireless device with a consistent user experience. At least a portion of the message that includes the state change information is sent to the other access routers identified in the received message, at **1006**. The same message or individual messages can be sent to the other access routers.

At **1008**, an acknowledgment is received from the other access routers in response to the message sent, at **1006**. Upon receipt of the acknowledgment(s), the method **1000** continues, at **1010**, with an optional acknowledgment sent to wireless terminal. Such an acknowledgment can notify wireless terminal that the access routers are synchronized with respect to the wireless terminal state. In some embodiments, an acknowledgment is not sent to the wireless terminal.

FIG. 11 illustrates a wireless device **1100** that communicates with an access router in accordance with the various embodiments. Wireless device **1100** includes a transmitter **1102** that can be configured to send a message to various devices including an access router. For example, the information conveyed can include a listing of access routers that wireless device **1100** communicates or it can be a multi-hop message that indicates a particular routing that the sent information could traverse. An optional formatter **1104** can be configured to include state change information in the message or an address of the wireless device **1100**, or other information that should be retained by an access router.

Wireless device **1000** also includes a receiver **1106** that can be configured to acquire various messages or subsets of messages, such as a return message. Receiver **1106**, in accordance with some embodiments, can receive an acknowledgment that indicates state synchronization among access routers that were indicated in a message sent by transmitter **1102**. Receiver **1106** can also be configured to acquire a state change notification from an access router or other network device.

An optional monitor **1108** can be included in wireless device **1100** that can track a predetermined interval that begins when a message is sent to an access router and ends when an acknowledgment is received in response to the message. If the acknowledgment is not received before expiration of the predetermined interval, a communication failure can be inferred. A subsequent message can be sent if a communication failure results.

FIG. 12 illustrates an access router **1200** that facilitates state synchronization. Access router **1200** can include a

17

receiver **1202**, a configurer **1204**, and a transmitter **1206** that can convey information to various devices (e.g., wireless terminals, access routers). Receiver **1202** can be configured to receive from a wireless device a message that includes access router information. The message from the wireless device can also include state change information, an acknowledgment request, or other information. Receiver **1202** can also be configured to accept information from other access routers, wherein such information can be state information, a reply to a previously sent message and/or an acknowledgment.

Configurer **1204** can modify a message received from a wireless device and/or an access router. For example, if the message does not include state information, configurer may append the message with the information. Thus, when the message is sent to one or more other access routers, through transmitter **1206**, the other access routers can automatically be updated with the state information. Configurer **1204** can also update or remove various information from the message prior to the message being transmitted to an access router and/or wireless device. Configurer **1204** can further reformat a message depending on the intended recipient.

FIG. **13** illustrates a block diagram of an apparatus **1300** for state change synchronization. Apparatus **1300** is represented as functional blocks, which can be functional blocks that represent functions implemented by a processor, software or combination thereof (e.g., firmware).

Apparatus **1300** includes a logical module **1302** for conveying a message to a first access router. The message can include an address of the first access router and an address for at least a second access router. Also included is a logical module **1304** for accepting at least a subset of the message from the second access router. The subset of the message can be an acknowledgment.

In some embodiments, apparatus **1300** can include a logical module **1306** for receiving a state change notification. Such a notification can be a state change of a wireless terminal. In some embodiments, apparatus **1300** includes a logical module **1308** for transmitting a state of the wireless terminal with the first message sent by logical module **1302**. Apparatus **1300** can include, in some embodiments, a logical module **1310** for including in the first message an address for the apparatus **1300**.

FIG. **14** illustrates a block diagram of an apparatus **1400** for synchronizing access routers with wireless terminal state change information. It should be noted that apparatus **1400** is represented as functional blocks, which can be functional blocks that represent functions implemented by a processor, software or combination thereof (e.g., firmware).

Included in apparatus **1400** is a logical module **1402** for acquiring a message from a wireless terminal. The message can include an address for a first access router, an address for a second access router, and an address for at least a third access router. Also included in the message can be a destination address for the wireless terminal. A logical module **1404** for communicating at least a subset of the message to the second access router is included in apparatus **1400**.

In some embodiments, apparatus **1400** can include a logical module **1406** for removing the address for the first access router from the message and a logical module **1408** for appending a state change of the wireless terminal to the message. In accordance with some embodiments, apparatus **1400** includes a logical module **1410** for notifying the wireless terminal of a state change (e.g., a terminal identification, a quality of service configuration, an authorization parameter, a timer associated with system use, a condition of a link) and a logical module **1412** for maintaining the state change for a subsequent communication with the wireless terminal.

18

FIG. **15** illustrates a block diagram of an apparatus **1500** that facilitates performance consistency of a wireless device. Apparatus **1500** is represented as functional blocks, which can be functional blocks that represent functions implemented by a processor, software or combination thereof (e.g., firmware).

Apparatus **1500** can include various logical modules to facilitate performance consistency. A logical module **1502** for accepting at a first access router a message from a second access router is included. The message can include a changed state of a wireless device, an address for the first access router, and an address for at least a third access router. In some embodiments, the message can include an identifier or address of the wireless device. Apparatus **1500** can also include a logical module **1504** for conveying at least a subset of the message to the third access router.

In some embodiments, apparatus **1500** can include a logical module **1506** for capturing or storing the changed state of the wireless device. Also included can be a logical module **1508** for applying the changed state to a subsequent communication with the wireless device.

FIG. **16** illustrates a block diagram of an apparatus **1600** that facilitates synchronization of wireless state information at an access router. Apparatus **1600** is represented as functional blocks, which can be functional blocks that represent functions implemented by a processor, software or combination thereof (e.g., firmware).

Apparatus **1600** can include a logical module **1602** for accepting at a first access router a communication from a second access router. The message can include an address of the first access router and a state of the wireless device. Also included can be a logical module **1604** for transmitting an acknowledgment of the communication to the wireless device.

In some embodiments, apparatus **1600** can include a logical module **1606** for maintaining the state of the wireless terminal at the first access router and a logical module **1608** for applying the state of the wireless device during a subsequent communication with the wireless device. In some embodiments, apparatus **1600** includes a logical module **1610** for removing the address of the first access router from the message prior to transmitting the acknowledgment to the wireless device.

Apparatus **1600** includes, in accordance with some embodiments, a logical module **1612** for determining if the message includes a second address for a third access router. Also included can be a logical module **1614** for communicating at least a subset of the message to the third access router.

FIG. **17** illustrates an exemplary communications system **1700** implemented in accordance with the various embodiments. Communications system **1700** includes multiple cells, labeled Cell **1** **1702** and Cell **M** **1704**, wherein **M** is an integer greater to or equal to one. Neighboring cells **1702**, **1704** can overlap slightly, as indicated by cell boundary region **1768**, thereby providing the potential for signal interference between signals being transmitted by base stations in neighboring cells. Each cell **1702**, **1704** of exemplary system **1700** includes three sectors. Cells which have not been subdivided into multiple sectors ( $N=1$ ), cells with two sectors ( $N=2$ ) and cells with more than three sectors ( $N>3$ ) are also possible in communications system **1700**. Cell **1** **1702** includes a first sector, sector **1** **1710**, a second sector, sector **2** **1712**, and a third sector, sector **3** **1714**. Each sector **1710**, **1712**, **1714** has two sector boundary regions; each boundary region is shared between two adjacent sectors. Sector boundary regions provide the potential for signal interference between signals being transmitted by base stations in neighboring sectors.

Line 1716 represents a sector boundary region between sector 1 1710 and sector 2 1712; line 1718 represents a sector boundary region between sector 2 1712 and sector 3 1714; line 1720 represents a sector boundary region between sector 3 1714 and sector 1 1710. Similarly, cell M 1704 includes a first sector, sector 1 1722, a second sector, sector 2 1724, and a third sector, sector 3 1726. Line 1728 represents a sector boundary region between sector 1 1722 and sector 2 1724; line 1730 represents a sector boundary region between sector 2 1724 and sector 3 1726; line 1732 represents a boundary region between sector 3 1726 and sector 1 1722.

Cell 1 1702 includes a base station (BS), base station 1 1706, and a plurality of end nodes (ENs) in each sector 1710, 1712, 1714. Sector 1 1710 includes EN(1) 1736 and EN(X) 1738 coupled to BS 1706 through wireless links 1740, 1742, respectively; sector 2 1712 includes EN(1') 1744 and EN(X') 1746 coupled to BS 1706 through wireless links 1748, 1750, respectively; sector 3 1714 includes EN(1'') 1752 and EN(X'') 1754 coupled to BS 1706 through wireless links 1756, 1758, respectively. Similarly, cell M 1704 includes base station M 1708, and a plurality of end nodes (ENs) in each sector 1722, 1724, 1726. Sector 1 1722 includes EN(1) 1736' and EN(X) 1738' coupled to BS M 1708 through wireless links 1740', 1742', respectively; sector 2 1724 includes EN(1') 1744' and EN(X') 1746' coupled to BS M 1708 through wireless links 1748', 1750', respectively; sector 3 1726 includes EN(1'') 1752' and EN(X'') 1754' coupled to BS M 1708 through wireless links 1756', 1758', respectively.

System 1700 also includes a network node 1760 which is coupled to BS 1 1706 and BS M 1708 through network links 1762, 1764, respectively. Network node 1760 is also coupled to other network nodes, (e.g., other base stations, AAA server nodes, intermediate nodes, routers, and the like) and the Internet through network link 1766. Network links 1762, 1764, 1766 may be, for example, fiber optic cables. Each end node (e.g. EN 1 1736) may be a wireless terminal including a transmitter as well as a receiver. The wireless terminals (e.g., EN(1) 1736) may move through system 1700 and may communicate through wireless links with the base station in the cell in which the EN is currently located. The wireless terminals, (WTs) (e.g. EN(1) 1736) may communicate with peer nodes (e.g., other WTs in system 1700 or outside system 1700) through a base station (e.g., BS 1706) and/or network node 1760. WTs (e.g., EN(1) 1736) may be mobile communications devices such as cell phones, personal data assistants with wireless modems, etc.

Each base station performs tone subset allocation using a different method for the strip-symbol periods, from a method employed for allocating tones and determining tone hopping in the rest symbol periods (e.g., non strip-symbol periods). The wireless terminals can use a tone subset allocation method along with information received from the base station, (e.g. base station slope ID, sector ID information) to determine the tones that they can use to receive data and information at specific strip-symbol periods. The tone subset allocation sequence is constructed, to spread the inter-sector and inter-cell interference across each of the tones.

FIG. 18 illustrates an exemplary base station implemented in accordance with the embodiments presented herein. Exemplary base station 1800 can implement a tone subset allocation sequence, with different tone subset allocation sequences generated for each different sector type of the cell. Base station 1800 may be used as any one of the base stations 1706, 1708 of the system 1700 of FIG. 17. The base station 1800 includes a receiver 1802, a transmitter 1804, a processor 1806, (e.g., CPU), an input/output interface 1807, a state management module 1808, a state management data 1809,

and memory 1810 which are coupled by a bus 1809 over which the various elements 1802, 1804, 1806, 1807, and 1810 may interchange data and information.

Sectorized antenna 1803 coupled to receiver 1802 is used for receiving data and other signals (e.g., state information, access router listing) from wireless terminals transmissions from each sector within the base station's cell. Sectorized antenna 1805 coupled to transmitter 1804 is used for transmitting data and other signals, (e.g., control signals, pilot signal, beacon signals, etc.) to wireless terminals 1900 (see FIG. 19) within each sector of the base station's cell. In various embodiments, base station 1800 may employ multiple receivers 1802 and multiple transmitters 1804, (e.g., an individual receiver 1802 for each sector and an individual transmitter 1804 for each sector). The processor 1806, may be, for example, a general purpose central processing unit (CPU). Processor 1806 controls operation of the base station 1800 under direction of one or more routines 1818 stored in memory 1810 and implements the disclosed methodologies. Input/Output (I/O) interface 1807 provides a connection to other network nodes, coupling the base station 1800 to other base stations, access routers, AAA server nodes, etc., other networks, and the Internet. State management module 1808 can send and/or receive messages for state synchronization. State management data 1809 can include information regarding the state data, keys, QoS, wireless terminal identifier, and the like.

Memory 1810 includes routines 1818 and data/information 1820. Data/information 1820 includes data 1836, tone subset allocation sequence information 1838 including downlink strip-symbol time information 1840 and downlink tone information 1842, and wireless terminal (WT) data/info 1844 including a plurality of sets of WT information: WT 1 info 1846 and WT N info 1860. Each set of WT info, (e.g., WT 1 info 1846) includes data 1848, terminal ID 1850, sector ID 1852, uplink channel information 1854, downlink channel information 1856, and mode information 1858.

Routines 1818 include communications routines 1822 and base station control routines 1824. Base station control routines 1824 includes a scheduler module 1826 and signaling routines 1828 including a tone subset allocation routine 1830 for the strip-symbol periods, other downlink tone allocation hopping routine 1832 for the rest of symbol periods, (e.g., non strip-symbol periods), and a beacon routine 1834.

Data 1836 includes data to be transmitted that will be sent to encoder 1814 of transmitter 1804 for encoding prior to transmission to WTs, and received data from WTs that has been processed through decoder 1812 of receiver 1802 following reception. Downlink strip-symbol time information 1840 includes the frame synchronization structure information, such as the superslot, beacons slot, and ultraslot structure information and information specifying whether a given symbol period is a strip-symbol period, and if so, the index of the strip-symbol period and whether the strip-symbol is a resetting point to truncate the tone subset allocation sequence used by the base station. Downlink tone information 1842 includes information including a carrier frequency assigned to the base station 1800, the number and frequency of tones, and the set of tone subsets to be allocated to the strip-symbol periods, and other cell and sector specific values such as slope, slope index and sector type.

Data 1848 may include data that WT 1 1900 has received from a peer node, data that WT 1 1900 desires to be transmitted to a peer node, and downlink channel quality report feedback information. Terminal ID 1850 is a base station 1800 assigned ID that identifies WT 1 1900. Sector ID 1852 includes information identifying the sector in which WT 1

## 21

1900 is operating. Sector ID 1852 can be used, for example, to determine the sector type. Uplink channel information 1854 includes information identifying channel segments that have been allocated by scheduler 1826 for WT1 1900 to use (e.g., uplink traffic channel segments for data, dedicated uplink control channels for requests, power control, timing control, etc.).

Each uplink channel assigned to WT1 1900 includes one or more logical tones, each logical tone following an uplink hopping sequence. Downlink channel information 1856 includes information identifying channel segments that have been allocated by scheduler 1826 to carry data and/or information to WT1 1900 (e.g., downlink traffic channel segments for user data). Each downlink channel assigned to WT1 1900 includes one or more logical tones, each following a downlink hopping sequence. Mode information 1858 includes information identifying the state of operation of WT1 1900, (e.g. sleep, hold, on).

Communications routines 1822 control the base station 1800 to perform various communications operations and implement various communications protocols. Base station control routines 1824 are used to control the base station 1800 to perform basic base station functional tasks (e.g., signal generation and reception, scheduling, and to implement the steps of the various methodologies including transmitting signals to wireless terminals using tone subset allocation sequences during the strip-symbol periods.

Signaling routine 1828 controls the operation of receiver 1802 with its decoder 1812 and transmitter 1804 with its encoder 1814. The signaling routine 1828 is responsible controlling the generation of transmitted data 1836 and control information. Tone subset allocation routine 1830 constructs the tone subset to be used in a strip-symbol period using the disclosed methodologies and data/info 1820 including downlink strip-symbol time info 1840 and sector ID 1852. The downlink tone subset allocation sequences will be different for each sector type in a cell and different for adjacent cells.

The WTs 1900 receive the signals in the strip-symbol periods in accordance with the downlink tone subset allocation sequences; the base station 1800 uses the same downlink tone subset allocation sequences in order to generate the transmitted signals. Other downlink tone allocation hopping routine 1832 constructs downlink tone hopping sequences, using information including downlink tone information 1842, and downlink channel information 1856, for the symbol periods other than the strip-symbol periods. The downlink data tone hopping sequences are synchronized across the sectors of a cell. Beacon routine 1834 controls the transmission of a beacon signal (e.g., a signal of relatively high power signal concentrated on one or a few tones), which may be used for synchronization purposes (e.g., to synchronize the frame timing structure of the downlink signal and therefore the tone subset allocation sequence with respect to an ultra-slot boundary).

FIG. 19 illustrates an exemplary wireless terminal (end node) 1900 which can be used as any one of the wireless terminals (end nodes) (e.g., EN(1) 1736, of the system 1700 shown in FIG. 17. Wireless terminal 1900 implements tone subset allocation sequences. The wireless terminal 1900 includes a receiver 1902 includes a decoder 1912, a transmitter 1903 including an encoder 1914, a state management module 1904 that can send/receive messages for state synchronization. Wireless terminal 1900 also includes a state management data 1905 that can include information regarding the state data, keys, QoS, wireless terminal identifier, and the like, and a processor 1906, and memory 1908 which are coupled by a bus 1910 over which the various elements 1902,

## 22

1903, 1904, 1905, 1906, 1908 can interchange data and information. An antenna 1903 used for receiving signals from a base station 1800 is coupled to receiver 1902. An antenna 1905 used for transmitting signals (e.g., to base station 1800) is coupled to transmitter 1903.

The processor 1906, (e.g., a CPU) controls the operation of the wireless terminal 1900 and implements methods by executing routines 1920 and using data/information 1922 in memory 1908. Data/information 1922 includes user data 1934, user information 1936, and tone subset allocation sequence information 1950. User data 1934 may include data, intended for a peer node, which will be routed to encoder 1914 for encoding prior to transmission by transmitter 1903 to base station 1800, and data received from the base station 1800 which has been processed by the decoder 1912 in receiver 1902. User information 1936 includes uplink channel information 1940, downlink channel information 1938, terminal ID information 1942, base station ID information 1944, sector ID information 1946, and mode information 1948.

Uplink channel information 1940 includes information identifying uplink channels segments that have been assigned by base station 1800 for wireless terminal 1900 to use when transmitting to the base station 1900. Uplink channels may include uplink traffic channels, dedicated uplink control channels (e.g., request channels, power control channels and timing control channels). Each uplink channel includes one or more logic tones, each logical tone following an uplink tone hopping sequence. The uplink hopping sequences are different between each sector type of a cell and between adjacent cells. Downlink channel information 1938 includes information identifying downlink channel segments that have been assigned by base station 1800 to WT 1900 for use when BS 1800 is transmitting data/information to WT 1900. Downlink channels may include downlink traffic channels and assignment channels, each downlink channel including one or more logical tone, each logical tone following a downlink hopping sequence, which is synchronized between each sector of the cell.

User info 1936 also includes terminal ID information 1942, which is a base station 1800 assigned identification, base station ID information 1944 that identifies the specific base station 1800 that WT has established communications with, and sector ID info 1946, which identifies the specific sector of the cell where WT 1800 is presently located. Base station ID 1944 provides a cell slope value and sector ID info 1946 provides a sector index type; the cell slope value and sector index type may be used to derive the uplink tone hopping sequences. Mode information 1948 also included in user info 1936 identifies whether the WT 1900 is in sleep mode, hold mode, or on mode.

Tone subset allocation sequence information 1950 includes downlink strip-symbol time information 1952 and downlink tone information 1954. Downlink strip-symbol time information 1952 include the frame synchronization structure information, such as the superslot, beaconslot, and ultraslot structure information and information specifying whether a given symbol period is a strip-symbol period, and if so, the index of the strip-symbol period and whether the strip-symbol is a resetting point to truncate the tone subset allocation sequence used by the base station. Downlink tone info 1954 includes information including a carrier frequency assigned to the base station 1800, the number and frequency of tones, and the set of tone subsets to be allocated to the strip-symbol periods, and other cell and sector specific values such as slope, slope index and sector type.

Routines **1920** include communications routines **1924** and wireless terminal control routines **1926**. Communications routines **1924** control the various communications protocols used by WT **1900**. Wireless terminal control routines **1926** controls basic wireless terminal **1900** functionality including the control of the receiver **1902** and transmitter **1903**. Wireless terminal control routines **1926** include the signaling routine **1928**. The signaling routine **1928** includes a tone subset allocation routine **1930** for the strip-symbol periods and an other downlink tone allocation hopping routine **1932** for the rest of symbol periods e.g., non strip-symbol periods). Tone subset allocation routine **1930** uses user data/info **1922** including downlink channel information **1940**, base station ID info **1944** (e.g., slope index and sector type), and downlink tone information **1954** in order to generate the downlink tone subset allocation sequences and process received data transmitted from base station **1800**. Other downlink tone allocation hopping routine **1930** constructs downlink tone hopping sequences, using information including downlink tone information **1954**, and downlink channel information **1940**, for the symbol periods other than the strip-symbol periods. Tone subset allocation routine **1930**, when executed by processor **1906**, is used to determine when and on which tones the wireless terminal **1900** is to receive one or more strip-symbol signals from the base station **1800**. The uplink tone allocation hopping routine **1930** uses a tone subset allocation function along with information received from the base station **1800**, to determine the tones in which it should transmit on.

It is to be understood that the embodiments described herein may be implemented by hardware, software, firmware, middleware, microcode, or any combination thereof. When the systems and/or methods are implemented in software, firmware, middleware or microcode, program code or code segments, they may be stored in a machine-readable medium, such as a storage component. A code segment may represent a procedure, a function, a subprogram, a program, a routine, a subroutine, a module, a software package, a class, or any combination of instructions, data structures, or program statements. A code segment may be coupled to another code segment or a hardware circuit by passing and/or receiving information, data, arguments, parameters, or memory contents. Information, arguments, parameters, data, etc., may be passed, forwarded, or transmitted using any suitable means including memory sharing, message passing, token passing, network transmission, etc.

For a software implementation, the techniques described herein may be implemented with modules (e.g., procedures, functions, and so on) that perform the functions described herein. The software codes may be stored in memory units and executed by processors. The memory unit may be implemented within the processor or external to the processor, in which case it can be communicatively coupled to the processor through various means as is known in the art.

What has been described above includes examples of one or more embodiments. It is, of course, not possible to describe every conceivable combination of components or methodologies for purposes of describing the aforementioned embodiments, but one of ordinary skill in the art may recognize that many further combinations and permutations of various embodiments are possible. Accordingly, the described embodiments are intended to embrace all such alterations, modifications and variations that fall within the spirit and scope of the appended claims. Furthermore, to the extent that the term "includes" is used in either the detailed description or the claims, such term is intended to be inclusive in a manner similar to the term "comprising" as "comprising" is interpreted when employed as a transitional word in a claim.

What is claimed is:

1. A method for a state change synchronization with multi-party handshake, the method comprising:
  - sending, from a wireless terminal, a first message to a first access router, wherein the first message includes a first indicator that identifies the first access router and a second indicator that identifies a second access router; and receiving, at the wireless terminal, an acknowledgment of the first message from the second access router, wherein the wireless terminal is an end node, and wherein a state change is a change in a state of the wireless terminal, and the first message indicates that there is the state change.
  2. The method of claim 1, further comprising receiving, at the wireless terminal, a notification of the state change from the first access router before the sending the first message.
  3. The method of claim 1, further comprising including, by the wireless terminal, the state of the wireless terminal in the first message.
  4. The method of claim 3, wherein the state of the wireless terminal is at least one of a condition of a link between the wireless terminal and the first access router, a terminal identification, a security key, a quality of service configuration, an authorization parameter, and a timer associated with system use.
  5. The method of claim 1, further comprising:
    - determining, by the wireless terminal, whether a pre-defined period has elapsed before the acknowledgment of the first message is received; and
    - resending, from the wireless terminal, the first message to the first access router if the pre-defined period has elapsed before the acknowledgment is received.
  6. The method of claim 1,
    - wherein the first access router is one of a base station, an access point, a packet data serving node (PDSN), and a gateway general packet radio services (GPRS) support node, and
    - wherein the second access router is one of a base station, an access point, a packet data serving node (PDSN), and a gateway general packet radio services (GPRS) support node.
  7. The method of claim 1, wherein sending the first message comprises sending the first message over an air link.
  8. An apparatus that facilitates a state synchronization among a plurality of access routers, the apparatus comprising:
    - a processor configured to transmit a communication to a first access router, wherein the communication includes a first address of a first access router and a second address of a second access router; and
    - a receiver configured to receive a completion message from the second access router, wherein the apparatus a wireless terminal which is an end node, and wherein a state change is a change in a state of the apparatus, and the communication indicates that there is the state change.
  9. The apparatus of claim 8, further comprising a memory configured to store information related to a plurality of access routers in communication with the apparatus.
  10. The apparatus of claim 8, further comprising:
    - a monitor configured to determine whether a specified period has elapsed before the completion message is received,
    - wherein the processor is configured to send a second communication to the first access router if the specified period has elapsed before the completion message is received,

25

wherein the second communication indicates that there is the state change.

11. The apparatus of claim 8, wherein the communication includes the state of the apparatus.

12. The apparatus of claim 8, wherein the processor is configured to transmit the communication in response to a notification of the state change received from the first access router.

13. The apparatus of claim 8, wherein the processor is configured to include an address of the apparatus in the communication.

14. The apparatus of claim 8, wherein the completion message is an acknowledgment of the communication indicating that the first and second access routers have been updated with state change information of the wireless terminal.

15. An apparatus for a state change synchronization, the apparatus comprising:

means for conveying a first message to a first access router, wherein the first message includes a first address of the first access router and a second address of a second access router; and

means for accepting at least a subset of the first message from the second access router,

wherein the apparatus is a wireless terminal which is an end node, and

wherein a state change is a change in a state of the apparatus, and the first message indicates that there is the state change.

16. The apparatus of claim 15, further comprising means for receiving a notification of the state change from the first access router prior to conveying the first message to the first access router.

17. The apparatus of claim 15, further comprising means for transmitting a state of the apparatus along with the first message.

18. The apparatus of claim 15, further comprising means for including in the first message a return address for the apparatus.

19. The apparatus of claim 15, further comprising:

means for tracking an expiration of a specified period;

means for determining if the subset of the first message is received from the second access router; and

means for conveying a second message to the first access router, if the specified period has expired and the subset of the first message is not received from the second access router,

wherein the second message indicates that there is the state change.

20. A non-transitory computer-readable medium having stored thereon computer-executable instructions for updating a plurality of access routers with state change information, wherein the instructions comprise:

communicating, from a wireless terminal, a message to a first access router, wherein the message includes a state change of the wireless terminal, a first address of the first access router, and a second address of a second access router; and

receiving, at the wireless terminal, an acknowledgment of the message from the second access router, wherein the wireless terminal is an end node.

21. The non-transitory computer-readable medium of claim 20, wherein the instructions further comprise including a return address of the wireless terminal in the message.

22. The non-transitory computer-readable medium of claim 20, wherein the instructions further comprise:

monitoring a defined interval until the acknowledgment is received;

26

identifying an expiration of the message if the defined interval passes before the acknowledgment is received; and

sending, from the wireless terminal, a second message to the first access router, wherein the second message includes the state change of the wireless terminal, the first address of the first access router, and the second address of the second access router.

23. A processor configured to execute computer-executable instructions for communicating a state change to a plurality of access routers, wherein the instructions comprise:

conveying a message to a first access router, wherein the message includes a first address of the first access router, a second address of a second access router, and a return address of a wireless device, and

acquiring at least a subset of the message from the second access router,

wherein the processor is a processor of the wireless device which is an end node, and

wherein the state change is a change in a state of the wireless device, and the message to the first access router indicates that there is the state change.

24. The processor of claim 23, wherein the instructions further comprise appending a changed state of the wireless device to the message prior to conveying the message to the first access router.

25. The processor of claim 23, wherein the instructions further comprise:

determining if the subset of the message is acquired before a specified interval has elapsed;

transmitting a second message to the first access router, if the specified interval has elapsed, wherein the second message includes the first address, the second address, and the return address; and

receiving at least a subset of the second message from the second access router.

26. A method for updating a plurality of access routers with terminal state information, the method comprising:

receiving, at a first access router, a message from a wireless device, the message including a first address of the first access router, a second address of a second access router and a third address of a third access router; and

routing at least a subset of the message to one of the second access router and the third access router,

wherein the wireless device is an end node,

wherein a state change is a change in a state of the wireless device, and the message received from the wireless device indicates that there is the state change, and

wherein the subset of the message routed to the second and/or the third access router includes the second address and/or the third address.

27. The method of claim 26, further comprising sending a state change notification to the wireless device, wherein the message received at the first access router is a response to the sent state change notification.

28. The method of claim 26, further comprising removing, at the first access router, the first address from the message before routing the subset of the message to the second access router such that the subset of the message comprises the message with the first address removed.

29. The method of claim 26, further comprising appending the message with a state of the wireless device before sending the subset of the message routed to the second and/or to the third access router such that the subset of the message includes the state of the wireless device.

30. A non-transitory computer-readable medium having stored thereon computer-executable instructions for a state

27

synchronization between a plurality of access routers utilizing multi-party handshake, wherein the instructions comprise:

accepting, at a first access router, a communication from a wireless terminal, wherein the communication includes a wireless terminal address, a first indicator that identifies the first access router, a second indicator that identifies a second access router, and a third indicator that identifies a third access router; and

transmitting at least a subset of the communication to the second access router,

wherein the wireless terminal is an end node,

wherein a state change is a change in a state of the wireless terminal, and the communication accepted from the wireless terminal indicates that there is the state change, and

wherein the subset of the message transmitted to the second access router includes the state of the wireless terminal and the second and third indicators.

**31.** The non-transitory computer-readable medium of claim **30**, wherein the instructions further comprise removing the first indicator, at the first access router, from the communication prior to transmitting the subset of the communication to the second access router.

**32.** The non-transitory computer-readable medium of claim **30**, wherein the instructions further comprise conveying a state change notification to the wireless terminal, wherein the communication is accepted in response to the conveyed state change notification.

**33.** A processor that executes computer-executable instructions for a state change synchronization, wherein the instructions comprise:

receiving a message from a wireless terminal, wherein the message includes a first address of a first access router, a second address of a second access router, and a third address of a third access router; and

conveying at least a subset of the message to the second access router,

wherein the wireless terminal is an end node,

wherein the processor is a processor of the first access router,

wherein a state change is a change in a state of the wireless terminal, and the message received from the wireless terminal indicates that there is the state change, and

wherein the subset of the message conveyed to the second access router includes the second and third addresses.

**34.** The processor of claim **33**, wherein the instructions further comprise notifying the wireless terminal of the state change, and the message is received in response to the notification.

**35.** The processor of claim **34**, wherein the instructions further comprise:

storing the state change in a retrievable format; and

applying the stored state change during a subsequent communication.

**36.** The processor of claim **33**, wherein the instructions further comprise:

removing the first address from the message; and

including the state of the wireless terminal and a destination address of the wireless terminal in the subset of the message prior to conveying the subset of the message to the second access router.

**37.** An apparatus that facilitates state information synchronization between access routers, the apparatus comprising:

a processor configured to receive a communication from a previous access router, wherein the communication

28

includes a state of a wireless device, a first address of a first access router, and a second address of a second access router;

a memory configured to store information related to the state of the wireless device; and

a transmitter configured to transmit at least a portion of the communication to the second access router,

wherein the wireless device is an end node,

wherein the apparatus is the first access router, and

wherein the portion of the communication transmitted to the second access router includes the second address and the state of the wireless device.

**38.** The apparatus of claim **37**, further comprising a modifier configured to mark the first address of the first access router as synchronized prior to the portion of the communication being transmitted to the second access router.

**39.** The apparatus of claim **37**, wherein the information stored is a change to the state of the wireless device.

**40.** A non-transitory computer-readable medium having stored thereon computer-executable instructions for state synchronization among access routers, wherein the instructions comprise:

acquiring a communication at a first access router from a previous access router, wherein the communication includes a first identification of the first access router and a second identification of a second access router, and a state of a wireless device; and

transmitting, from the first access router, at least a subset of the communication to the second access router,

wherein the wireless device is an end node, and

wherein the portion of the communication transmitted to the second access router includes the second identification and the state of the wireless device.

**41.** The non-transitory computer-readable medium of claim **40**, wherein the instructions further comprise storing the state of the wireless device at the first access router.

**42.** The non-transitory computer-readable medium of claim **40**, wherein the instructions further comprise one of removing the first identification from the communication and marking the first identification as synchronized prior to transmitting the subset of the communication.

**43.** An apparatus that facilitates a state synchronization of a second access router, the apparatus comprising:

a processor configured to receive a message that from a first access router, wherein the message includes a wireless device state information of a wireless device;

a memory configured to store the wireless device state information in a retrievable format; and

a transmitter configured to transmit at least a subset of the message to the wireless device as an acknowledgment of a successful receipt of the message,

wherein the wireless device is an end node, and

wherein the apparatus is the second access router.

**44.** The apparatus of claim **43**, further comprising a modifier configured to mark as synchronized an address of the second access router included in the message prior to the subset of the message being transmitted to the wireless device.

**45.** The apparatus of claim **43**, wherein the second access router in communication with the wireless device.

**46.** A processor configured to execute computer-executable instructions for a state synchronization of an access router, wherein the instructions comprise:

accepting, at a second access router, a message from a first access router, wherein the message includes an address of the second access router and a changed state of a wireless device; and



## 29

outputting to the wireless device at least a subset of the message,  
 wherein the wireless device is an end node, and  
 wherein the processor is a processor of the second access router.

47. The processor of claim 46, wherein the instructions further comprise modifying the message to mark the address of the second access router as synchronized.

48. The processor of claim 46, wherein the instructions further comprise modifying the message to include an acknowledgment that the message was successfully received at the first access router.

49. The method of claim 1, wherein the first access router and the second access router are among a plurality of access routers with which the wireless terminal can communicate without a handoff.

50. The apparatus of claim 8, wherein the first access router and the second access router are among the plurality of access routers with which the apparatus can communicate without a handoff.

51. The apparatus of claim 15, wherein the first access router and the second access router are among a plurality of access routers with which the apparatus can communicate without a handoff.

52. The non-transitory computer-readable medium of claim 20, wherein the first access router and the second access router are among the plurality of access routers with which the wireless terminal can communicate without a handoff.

53. The processor of claim 23, claim 20, wherein the first access router and the second access router are among the plurality of access routers with which the wireless device can communicate without a handoff.

## 30

54. The method of claim 26, wherein the first access router, the second access router and the third access router are among the plurality of access routers with which the wireless device can communicate without a handoff.

55. The non-transitory computer-readable medium of claim 30, wherein the first access router, the second access router and the third access router are among a plurality of access routers with which the wireless terminal can communicate without a handoff.

56. The processor of claim 33, wherein the first access router, the second access router and the third access router are among a plurality of access routers with which the wireless terminal can communicate without a handoff.

57. The apparatus of claim 37, wherein the first access router and the second access router are among a plurality of access routers with which the wireless device can communicate without a handoff.

58. The non-transitory computer-readable medium of claim 40, wherein the first access router and the second access router are among a plurality of access routers with which the wireless device can communicate without a handoff.

59. The apparatus of claim 43, wherein the first access router and the second access router are among a plurality of access routers with which the wireless device can communicate without a handoff.

60. The processor of claim 46, wherein the first access router and the second access router are among a plurality of access routers with which the wireless device can communicate without a handoff.

\* \* \* \* \*